




3F11-100

SNAP DISC AUTOMATIC RESET FAN LIMITS

1/2" Automatic reset snap disc thermostats for appliance and HVAC.

FEATURES

- Loose ring, stainless steel mounting brackets
- 1/4" quick connect terminals
- Aluminum disc cup
- Last three numbers indicate cut-in temperatures on fan controls and cut-out temperatures on limits



SPECIFICATIONS

Switch Action SPST Open or Close on Rise
 Electrical Ratings Resistive 15A @ 120 VAC, 10A @ 240 VAC,
 Inductive 3.0 FLA, 12.0LRA @ 120 VAC; 1.5FLA, 6.0LRA @ 240 VAC
 Pilot Duty 125 VA
 Dimensions37\"/>

SNAP DISC AUTOMATIC RESET FAN LIMITS

| APPLICATION | CUT-IN | CUT-OUT | SWITCH ACTION | DIFFERENTIAL | THERM-O-DISC TYPE | THERM-O-DISC STYLE | MODEL NUMBER | ITEM NUMBER |
|-----------------------------------|---------------|---------------|---------------|--------------|-------------------|--------------------|--------------|-------------|
| Snap Disc Fan - Automatic Reset | 100°F (38°C) | 70°F (21°C) | Close on rise | 30°F (17°C) | 36T22 | 10844 | 3F11-100 | 03F11 100 |
| | 120°F (49°C) | 90°F (32°C) | Close on rise | 30°F (17°C) | 36T22 | 10847 | 3F11-120 | 03F11 120 |
| | 140°F (60°C) | 110°F (43°C) | Close on rise | 30°F (17°C) | 36T22 | 10849 | 3F11-140 | 03F11 140 |
| | 170°F (77°C) | 140°F (60°C) | Close on rise | 30°F (17°C) | 36T22 | 10853 | 3F11-170 | 03F11 170 |
| | 180°F (82°C) | 150°F (66°C) | Close on rise | 30°F (17°C) | 36T22 | 10856 | 3F11-180 | 03F11 180 |
| | 225°F (107°C) | 195°F (91°C) | Close on rise | 30°F (17°C) | 36T22 | 10860 | 3F11-225 | 03F11 225 |
| | 240°F (116°C) | 140°F (60°C) | Close on rise | 100°F (56°C) | 36T22 | 10862 | 3F11-240 | 03F11 240 |
| Snap Disc Limit - Automatic Reset | 40°F (4°C) | 60°F (16°C) | Open on rise | 20°F (12°C) | 36T21 | 10842 | 3L11-60 | 03L11 060 |
| | 70°F (21°C) | 85°F (29°C) | Open on rise | 15°F (8°C) | 36T21 | 10843 | 3L11-85 | 03L11 085 |
| | 110°F (43°C) | 80°F (27°C) | Open on rise | 30°F (17°C) | 36T21 | 10845 | 3L11-110 | 03L11 110 |
| | 90°F (32°C) | 120°F (49°C) | Open on rise | 30°F (17°C) | 36T21 | 10846 | 3L11-120 | 03L11 120 |
| | 110°F (43°C) | 140°F (60°C) | Open on rise | 30°F (17°C) | 36T21 | 10848 | 3L11-140 | 03L11 140 |
| | 120°F (49°C) | 150°F (66°C) | Open on rise | 30°F (17°C) | 36T21 | 10850 | 3L11-150 | 03L11 150 |
| | 130°F (54°C) | 160°F (71°C) | Open on rise | 30°F (17°C) | 36T21 | 10851 | 3L11-160 | 03L11 160 |
| | 140°F (60°C) | 170°F (77°C) | Open on rise | 30°F (17°C) | 36T21 | 10852 | 3L11-170 | 03L11 170 |
| | 160°F (71°C) | 175°F (79°C) | Open on rise | 15°F (8°C) | 36T21 | 10854 | 3L11-175 | 03L11 175 |
| | 150°F (66°C) | 180°F (82°C) | Open on rise | 30°F (17°C) | 36T21 | 10855 | 3L11-180 | 03L11 180 |
| | 160°F (71°C) | 190°F (88°C) | Open on rise | 30°F (17°C) | 36T21 | 10857 | 3L11-190 | 03L11 190 |
| | 180°F (82°C) | 210°F (99°C) | Open on rise | 30°F (17°C) | 36T21 | 10858 | 3L11-210 | 03L11 210 |
| | 190°F (88°C) | 220°F (104°C) | Open on rise | 30°F (17°C) | 36T21 | 10859 | 3L11-220 | 03L11 220 |
| | 200°F (93°C) | 230°F (110°C) | Open on rise | 30°F (17°C) | 36T21 | 10861 | 3L11-230 | 03L11 230 |
| | 220°F (104°C) | 250°F (121°C) | Open on rise | 30°F (17°C) | 36T21 | 10863 | 3L11-250 | 03L11 250 |
| 275°F (135°C) | 325°F (163°C) | Open on rise | 50°F (28°C) | 36T21 | 10864 | 3L11-325 | 03L11 325 | |