

# DELTA PARTS NUMBERING SYSTEM

## MODELS OTHER THAN POWER ENTRY MODULE TYPES AND P.C. BOARD MOUNTING TYPES

<u>03</u>	<u>GE</u>	<u>E</u>	<u>G3</u>	<u>V</u>	<u>-R</u>

**Option resistor**

**Design sequence:**  
 (for cylinder types, the 8th digit designates the outside diameter; S- ∅38mm; M- ∅43mm; L- ∅50mm)

**Input/Output connection:**  
 G = lugs; W = PVC wires; S = screws  
 G5 = 5 lugs (6.3\*0.8mm)  
 W5 = 5 wires (UL 1015 AWG#18, 4" long)

**Case style:**  
 A- Small mounting ears 90 degrees from terminal sides  
 B- Triangle mounting ears 90 degrees from terminal sides  
 C- Triangle mounting ears on terminal sides  
 D- IEC connector with mounting screws  
 E- IEC connector package  
 F- Cylinder types  
 G- Two-hole mounting bars, 90 degrees from terminal sides  
 N- IEC connector with snap-in type

**Series:** Electrical circuit, see specific catalog pages

**Current rating:** AC rms  
 e.g.: 03 amp

## POWER ENTRY MODULE TYPES

<u>06</u>	<u>AR</u>	<u>2</u>	<u>D</u>	

**Special design:**  
 A- with ground choke  
 D- with double pole power switch for models AB, AK, AR series

**Module construction:**  
 1- IEC connector & fuse holder  
 2- IEC connector, fuse holder and power switch  
 3- IEC connector, fuse holder, power switch and voltage selector switch  
 4- IEC connector, fuse holder & voltage selector switch  
 5- For models other than CK, CR series; same construction as 4 but with voltage selector switch at front panel

**Series:** Electric circuit, see specific catalog pages

**Current rating:** AC rms  
 e.g.: 06 amp

## PCB MOUNTING TYPES

<u>03</u>	<u>ME</u>	<u>3</u>	<u>A</u>	<u>-R</u>

**Option resistor**

**Special design:**  
 A: with ground choke

**Design sequence**

**Series:** Electrical circuit, see specific catalog page

**Current rating:** AC rms  
 e.g. :03 amp

# DELTA PARTS NUMBERING SYSTEM

## 3-Phase Types

10

TD

S6

D

**Current rating:** AC rms  
e.g.: 10 amp

**Series:**

- TD: used in "Δ" system
- TDH: used in "Δ" system
- TDR: used in "Δ" system, vertical style
- TDV: used in "Δ" system, vertical style
- TDS: used in "Δ" system, screw style
- TY: used in both "Δ" & "y" system
- TYS: used in "Δ" & "y" system, screw style
- TYT: used in "Δ" & "y" system terminal block style
- PT: P.C.B. Filter
- PY: P.C.B. Filter

**Input/Output connection :**

- G = lugs; W = PVC wires; S = screws; T = terminal blocks
- e.g.
- G6 = 6 lugs
- W6 = 6 wires
- T2: 2 terminal blocks
- TIW4: 1 terminal block / 4 wires

**Special Design:**  
Dual: diff. and common choke

