

# DELTA PARTS NUMBERING SYSTEM

## MODELS OTHER THAN POWER ENTRY MODULE TYPES AND P.C. BOARD MOUNTING TYPES

<u>03</u>	<u>GE</u>	<u>E</u>	<u>G3</u>	<u>V</u>	<u>-R</u>
					Option resistor  <b>Design sequence:</b> (for cylinder types, the 8th digit designates the outside diameter; S- $\varnothing$ 38mm; M- $\varnothing$ 43mm; L- $\varnothing$ 50mm)
					<b>Input/Output connection:</b> G = lugs; W = PVC wires; S = screws G5 = 5 lugs (6.3*0.8mm) W5 = 5 wires (UL 1015 AWG#18, 4" long)
					<b>Case style:</b> A- Small mounting ears 90 degrees from terminal sides B- Triangle mounting ears 90 degrees from terminal sides C- Triangle mounting ears on terminal sides D- IEC connector with mounting screws E- IEC connector package F- Cylinder types G- Two-hole mounting bars, 90 degrees from terminal sides N- IEC connector with snap-in type
Series: Electrical circuit, see specific catalog pages					
Current rating: AC rms e.g.: 03 amp					

## POWER ENTRY MODULE TYPES

<u>06</u>	<u>AR</u>	<u>2</u>	<u>D</u>
			<b>Special design:</b> A- with ground choke D- with double pole power switch for models AB, AK, AR series
			<b>Module construction:</b> 1- IEC connector & fuse holder 2- IEC connector, fuse holder and power switch 3- IEC connector, fuse holder, power switch and voltage selector switch 4- IEC connector, fuse holder & voltage selector switch 5- For models other than CK, CR series; same construction as 4 but with voltage selector switch at front panel
Series: Electric circuit, see specific catalog pages			
Current rating: AC rms e.g.: 06 amp			

## PCB MOUNTING TYPES

<u>03</u>	<u>ME</u>	<u>3</u>	<u>A</u>	<u>-R</u>
				Option resistor  <b>Special design:</b> A: with ground choke
				<b>Design sequence</b>
Series: Electrical circuit, see specific catalog page				
Current rating: AC rms e.g. :03 amp				

# DELTA PARTS NUMBERING SYSTEM

## 3-Phase Types

10

TD

S6

D

**Current rating:** AC rms  
e.g.: 10 amp

**Series:**

- TD: used in "Δ" system
- TDH: used in "Δ" system
- TDR: used in "Δ" system, vertical style
- TDV: used in "Δ" system, vertical style
- TDS: used in "Δ" system, screw style
- TY: used in both "Δ" & "y" system
- TYS: used in "Δ" & "y" system, screw style
- TYT: used in "Δ" & "y" system terminal block style
- PT: P.C.B. Filter
- PY: P.C.B. Filter

**Input/Output connection :**

- G = lugs; W = PVC wires; S = screws; T = terminal blocks
- e.g.
- G6 = 6 lugs
- W6 = 6 wires
- T2: 2 terminal blocks
- TIW4: 1 terminal block / 4 wires

**Special Design:**

Dual: diff. and common choke

