



All dimensions are in mm; tolerances according to ISO 2768 m-H

### Interface

According to IEC 61169-40  
Mechanically compatible with RPC-1.85

### Documents

Assembly instruction 02 A3

### Material and plating

#### Connector parts

Center contact  
Outer contact  
Coupling Nut  
Dielectric  
Solder sleeve

#### Material

CuBe  
Stainless steel  
Stainless steel  
PEEK  
Brass

#### Plating

Gold, min. 1.27  $\mu\text{m}$ , over chemical nickel  
Passivated  
Passivated  
Gold, 0.1  $\mu\text{m}$  min.

RPC-2.40

Straight plug

**09S121-271S3**

**Electrical data**

Impedance	50 Ω
Frequency	DC to 50 GHz
Return loss	≥ 23 dB, DC to 50 GHz
Insertion loss	≤ 0.05 x √f(GHz) dB
Insulation resistance	≥ 5 GΩ
Test voltage (at sea level)	500 V rms
Working voltage (at sea level)	150 V rms
RF-leakage	≥ 100 dB up to 1 GHz

- Limitations are possible due to the used cable type -

**Mechanical data**

Mating cycles	≥ 500
Center contact captivation	≥ 20 N
Coupling test torque	1.65 Nm
Recommended torque	0.80 Nm to 1.10 Nm

**Environmental data**

Temperature range	-40°C to +85°C
Thermal shock	IEC 61169-1, Subclause 9.4.4
Corrosion	IEC 61169-1, Subclause 9.4.6
Vibration	IEC 61169-1, Subclause 9.3.3
Shock	IEC 61169-1, Subclause 9.3.14
Moisture resistance	IEC 61169-1, Subclause 9.4.3
RoHS	compliant

**Tooling**

N/A

**Suitable cables**

UT 85, RG 405 /U, RTK-FS 085

**Weight**

9.2 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Herbert Babinger	26.08.04	F. Reiner	20.06.18	c01	18-1026	M.Ruf	20.06.18

Rosenberger Hochfrequenztechnik GmbH & Co. KG  
 P.O.Box 1260 D-84526 Tittmoning Germany  
[www.rosenberger.de](http://www.rosenberger.de)

Tel. : +49 8684 18-0  
 Email : [info@rosenberger.de](mailto:info@rosenberger.de)

Page  
 2 / 2