# **Gore Cable Assembly Builder**


## Microwave Assembly Part Number 0Z0CJ0CJ0480

W. L. Gore & Associates has developed and proven a wide range of products specifically tailored to the RF / microwave industry. Since 1976, when Gore first introduced our microwave assemblies, Gore has remained a worldwide leader in providing custom microwave assemblies for demanding applications. Typical applications using GORE & Microwave Assemblies include: test, aerospace, defense, telecommunications and general purpose. With an unmatched history in demanding environments, you may be assured that Gore will provide the reliable products necessary to meet your individual system requirements.

GORE<sup>TM</sup> Mini-CP Cable is internally ruggedized with excellent phase and amplitude stability. With the ruggedization designed into the cable, the assemblies have excellent durability while remaining exceptionally lightweight and flexible. The exceptional performance of mini-cp cable enables accurate and repeatable measurements while limiting the need to perform time consuming calibrations between measurements.

#### **Specifications**

Max Frequency GHz	50
Impedance Ohms	50
Center Conductor	Solid
Dielectric Constant (nominal)	1.4
Velocity of Propagation	0.85
Temperature °C	-55 to 125
Nominal Outer Diameter in. (mm)	0.240 (6.1)
Minimum Bend Radius (multiple bends) in. (mm)	1 (25.4)
Nominal Weight g/ft (g/m)	31 (101.7)
Crush Resistance lb/linear in.	250
Typical Insertion Loss dB at 50GHz	-5.0549
Guaranteed Insertion Loss dB at 50GHz	-6.3396
Guaranteed VSWR at 50GHz	1.43:1
Guaranteed Return Loss dB	-15.00
Phase Stability +/- °	11.81
Amplitude Stability +/- dB	0.25




### **Key Features**

- Phase and amplitude stability
- Crush, torque and kink resistant
- Phase matching options
- · Replaceable interface options/adapters

#### **Key Benefits**

- Longer calibration intervals
- Longer field-service life
- Suited for parallel or comparative measurements
- Reduced risk of assembly damage

# **Typical Insertion Loss**



## **Guaranteed Insertion Loss**

