


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
	A3	REVISED PER ECR-20-013028	14SEP2020	MM DD

NOTES:

- 1 MATERIALS AND FINISH:
 -MODULE HOUSING: PBT, COLOR: GREY
 -CONTACTS: BRASS, FINISH: Sn
 -O-RING: SILICON RUBBER
- 2. MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)
- 3 LOCATION OF FLAT ON RECEPTACLE (TE P/N 2213858-1)
 THREAD SECTION IN FULL MATED POSITION
- 4. COMPATIBLE DOME IS 2328823-X.
- 5. MATES WITH RECEPTACLE ASSEMBLIES 2343403-1 OR 1-2343403-1.
- 6. RECOMMENDED PIN OUT FOR 0-10V DIMMING CONTROL APPLICATIONS:

PIN	0-10V CONTROL
1	DC+
2	0-10V DIM- DC-
3	0-10V DIM+
4	OPTIONAL




SCALE 3:2

MODULE BASE ASSY,CLOSED VENT,KEY A	2-2343404-1
MODULE BASE ASSY,VENT,KEY A	1-2343404-1
DESCRIPTION AND KEYING	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C DAILY 03OCT2018	TE Connectivity	
		CHK E HOWARD 03OCT2018		
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD -	NAME MODULE BASE ASSEMBLY, LUMAWISE ENDURANCE S 80mm DIAMETER,KEYED	
	0 PLC ±	PRODUCT SPEC	RESTRICTED TO	
	1 PLC ±0.2	108-133073	SIZE	A2
	2 PLC ±0.15	APPLICATION SPEC	CAGE CODE	-
	3 PLC ±	114-133074	DRAWING NO	G-2343404
	4 PLC ±	WEIGHT	SCALE	2:1
	ANGLES ±1		SHEET	1 OF 4
MATERIAL	FINISH	CUSTOMER DRAWING	REV	A3
SEE NOTES				

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
-	-	SEE SHEET 1	-	-




1-2343404-1 SHOWN


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C. DAILY 03OCT2018	STE TE Connectivity															
		CHK E. HOWARD 03OCT2018																
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD -														
<table border="1"> <tr><td>0 PLC</td><td>±</td></tr> <tr><td>1 PLC</td><td>±0.2</td></tr> <tr><td>2 PLC</td><td>±0.15</td></tr> <tr><td>3 PLC</td><td>±</td></tr> <tr><td>4 PLC</td><td>±</td></tr> <tr><td>ANGLES</td><td>±1</td></tr> <tr><td>FINISH</td><td>-</td></tr> </table>		0 PLC	±	1 PLC	±0.2	2 PLC	±0.15	3 PLC	±	4 PLC	±	ANGLES	±1	FINISH	-	PRODUCT SPEC 108-133073		NAME MODULE BASE ASSEMBLY, LUMAWISE ENDURANCE S 80mm DIAMETER, KEYED
0 PLC	±																	
1 PLC	±0.2																	
2 PLC	±0.15																	
3 PLC	±																	
4 PLC	±																	
ANGLES	±1																	
FINISH	-																	
MATERIAL - SEE NOTES		APPLICATION SPEC 114-133074		SIZE A2														
		WEIGHT -		CAGE CODE -														
		CUSTOMER DRAWING		DRAWING NO. G-2343404														
		SCALE 2:1		RESTRICTED TO -														
		SHEET 2 OF 4		REV A3														

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
-		SEE SHEET 1	-	-




CONTACT SOLDER
TAILS SEALED
4X




CONTACT SOLDER
TAILS SEALED
4X

VENT HOLE
BLOCKED



NOTE: KEY



NOTE: KEY

1-2343404-1 SHOWN

2-2343404-1 SHOWN

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C. DAILY 03OCT2018	TE Connectivity	
		CHK E. HOWARD 03OCT2018		
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD -
		0 PLC ±	1 PLC ±0.2	PRODUCT SPEC
		2 PLC ±0.15	3 PLC ±	108-133073
		4 PLC ±	ANGLES ±1	APPLICATION SPEC
		FINISH -		114-133074
MATERIAL -				WEIGHT -
SEE NOTES				CUSTOMER DRAWING
		NAME MODULE BASE ASSEMBLY, LUMAWISE ENDURANCE S 80mm DIAMETER, KEYED		RESTRICTED TO -
		SIZE A2	CAGE CODE -	DRAWING NO. G-2343404
		SCALE 2:1	SHEET 3 OF 4	REV A3