1020YH 10.1" LCD Display Monitor with HDMI, DVI, VGA & AV Inputs



Description

Xenarc Technologies Corp. was the first to introduce a **10.1" LCD screen with VGA and HDMI inputs**, and now we have further improved this popular industrial-grade model by incorporating the latest LED backlight technology. In addition, Solid Capacitors are used in place of Electrolytic Capacitors though out the unit to further improve the stability and durability especially in extreme temperature conditions. This **10.1" Industrial Display Monitor unit** is available with a Touch Screen as the 1020TSH. It is also available with 1000NIT direct sunlight readability as the 1022YH.

Don't mistake this **industrial**, **heavy duty**, **rugged 10.1" display monitor** for an ordinary video monitor that displays composite video. This **10.1" display monitor** has 1024 x 600 pixels (3072 x 600 sub-pixels) that help display crystal clear text and ultra-sharp images through your computer's VGA or HDMI signal.

The brushed, anodized aluminum face plate gives the display a futuristic yet elegant look. The entire enclosure is constructed with aluminum, making the unit both strong and light weight and the thin profile (only 1.19") makes the display very compact with a small footprint. Our displays are designed for applications such as but not limited to:

- Transportation Marine, Air, Heavy Vehicles, Mining, Weigh Stations, Fleet Management, Telematics, In-Car Computing, Public Transit, Cargo
- System Integration Machinery Controls, Factory Automation, Environmental Monitoring, Home Automation, Military, Smart Home
- Point of Sale Hospitality, Digital Signage, Self-Service Kiosks, Outdoor Kiosks and Signage, Casino
- **Data Monitoring** Cloud, IoT, Medical, Logistics, Inventory Management, Oil & Gas/Utilities, Law Enforcement, Broadcasting, Veterinary, First Person View
- Broadcast & Production Broadcast Stations, Mobile Production Vehicles, Field Rugged Deployment for your mobile workforce, Studio Video Production

Features

- 400NIT High Brightness Long Life LED Backlight
- Automatic Backlight Adjustment through Built-in Ambient Light Sensor
- Anti-Glare Coating
- HDMI Input x 1 (HDCP), VGA Input (15 pin D-SUB) x 1 & Video Input x 2
- Audio Input x 3 / Built-In Speakers
- 1024x600 Native Resolution, 16x9 Aspect Ratio
- Solid Capacitors for Improved Durability
- High Performance Image and Video Signal Processor
- AISS Advanced Image-Scaling and Shaping
- Last Input and Power Setting Memory
- IR Remote Control
- Auto Power-On upon signal detection
- Vertical Image Flip
- Function to Disable Front Button(s) and On Screen Text
- AV2 Auto Switching for Backup Camera
- 360° Copper Monitor Stand or U-Shape Mount
- VESA 75mm Mounting Holes
- 26-Pin Heavy-Duty Connector with Connector Locking
- Ruggedized Aluminum Casing
- Supports 9V DC ~ 36V DC
- "E" Mark Certified for Automotive use
- FCC, CE, E13 Certification