



DESIGNED FOR USE WITH RG-178, 196	
CABLE ENTRY DIAMETER MINIMUM	
FERRULE	.081
HOUSING	.036
CONTACT SLOT	.025

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 <sub>3</sub>	REVISED	K.L. 8-2-96 877196	<i>[Signature]</i>

HOUSING COUPLING NUT CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204

COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		
FRAC. ± 1/64	DEC. ± .005	ANGLES ± 1°
DRAWN BY SK		DATE 11-18-77
CHECKED BY OBG		DATE 12-2-77
APPD BY		
USE ASSY PROCEDURE		TITLE
408-04799 NO. AP. (10-013)		OSSM RIGHT ANGLE CABLE PLUG - SOLDER ATTACHMENT
SIZE B	CODE IDENT NO. 26805	1037-5001-00
SCALE 5:1	REV 01 <sub>3</sub>	
SHEET 1 OF 1		

.XXX = in  
XX.X = mm (REF)

NOTES:  
1. CAPTURED CENTER CONTACT

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.



AMP Incorporated  
140 Fourth Avenue  
Waltham, MA 02451-7599