



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 ₀	PART NO WAS 4562-0000-00 PER ECN 84-0476	LR 8/16/84	D.CAM
02 ₁	REDRAWN ON CAD PER ECN 88-0678	BME 2/7/90	BB 2/9/90
B	PER EC 0U20-0262-01	10/19/01	C. Hoang
D	PER EC 0S14-0146-02	GV 21MAY03	JGH

NOTES:
1. CAPTURED CENTER CONTACT

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions per <u>DESC spec 85701</u>	TEMPERATURE RATING <u>-65°C TO +125°C</u>
Frequency Range (GHz) <u>DC-18</u>	Recommended Mating Torque <u>N/A</u>	Vibration - MIL-STD-202, Method 204, Condition D
Volt Rating (VRMS MAX) <u>500 @ Sea level</u>	Mating Characteristics: Insertion (MAX Lbs) <u>N/A</u>	Shock - MIL-STD-202, Method 213, Condition I
VSWR <u>N/A</u>	Withdrawal (MIN Oz) <u>N/A</u>	Thermal shock MIL-STD-202, Method 107 Test Condition B
Insertion Loss (dB MAX) <u>N/A</u>	Connector Engagement and Disengagement (In/Lbs MAX) <u>N/A</u>	EXCEPT HIGH TEMP 115°C
RF Leakage (dB MIN) <u>-(90-F)(GHz)</u> (Interface only, fully mated)	Center Contact Captivation: Axial <u>6 Lbs</u>	Moisture Resistance - MIL-STD-202, Method 106
Corona, 70,000 Ft (VRMS MIN) <u>335</u>	Radial <u>None</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Dielectric Withstanding Voltage (VRMS MIN) <u>1000</u>	Cable Retention: Axial Force <u>N/A</u>	
Contact Resistance (Milliohms MAX): Center Contact <u>2.0</u>	Torque <u>N/A</u>	
Outer Contact <u>2.0</u>	Weight (Grams) _____	
RF High Potential (VRMS MIN @ 5 MHz) <u>1000</u>		
I.R.(Megohms) <u>5000 MIN</u>		

COMPONENT	MATERIAL	FINISH
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457, MIL-P-19468, AND FED. SPEC L-P-403	N/A
CENTER CONTACT	BRASS PER ASTM B 16	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
"O" - RING	FLOUROSILOCONE PER-MIL-R-25988, CLASS 1, TYPE 1	N/A

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES + 1/64 + .005 + 1°	DRAWN BY JDP	DATE 2-9-83	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY T.SCANNELLI	9/29/83	
These drawings and specifications are the property of Dnni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	APPROVED BY T.SCANNELLI	9/29/83	AMP
	USE ASS'Y PROCEDURE		
NO. A.P. <u>N/A</u>	TITLE <u>DSP PRINTED CIRCUIT BOARD PLUG RECEPTACLE - STRAIGHT TERMINAL</u>		
	SIZE <u>B</u>	CODE IDENT NO. <u>26805</u>	REV <u>02₁</u>
	SCALE <u>5:1</u>	SHEET 1 OF 1	

CUSTOMER DRAWING

AMP PART # 1058577-1
SHEET 1 OF 1 REV D