

DELTA PARTS NUMBERING SYSTEM

MODELS OTHER THAN POWER ENTRY MODULE TYPES AND P.C. BOARD MOUNTING TYPES

<u>03</u>	<u>GE</u>	<u>E</u>	<u>G3</u>	<u>V</u>	<u>-R</u>
					Option resistor Design sequence: (for cylinder types, the 8th digit designates the outside diameter; S- \varnothing 38mm; M- \varnothing 43mm; L- \varnothing 50mm)
					Input/Output connection: G = lugs; W = PVC wires; S = screws G5 = 5 lugs (6.3*0.8mm) W5 = 5 wires (UL 1015 AWG#18, 4" long)
					Case style: A- Small mounting ears 90 degrees from terminal sides B- Triangle mounting ears 90 degrees from terminal sides C- Triangle mounting ears on terminal sides D- IEC connector with mounting screws E- IEC connector package F- Cylinder types G- Two-hole mounting bars, 90 degrees from terminal sides N- IEC connector with snap-in type
Series: Electrical circuit, see specific catalog pages					
Current rating: AC rms e.g.: 03 amp					

POWER ENTRY MODULE TYPES

<u>06</u>	<u>AR</u>	<u>2</u>	<u>D</u>		
				Special design: A- with ground choke D- with double pole power switch for models AB, AK, AR series	
				Module construction: 1- IEC connector & fuse holder 2- IEC connector, fuse holder and power switch 3- IEC connector, fuse holder, power switch and voltage selector switch 4- IEC connector, fuse holder & voltage selector switch 5- For models other than CK, CR series; same construction as 4 but with voltage selector switch at front panel	
Series: Electric circuit, see specific catalog pages					
Current rating: AC rms e.g.: 06 amp					

PCB MOUNTING TYPES

<u>03</u>	<u>ME</u>	<u>3</u>	<u>A</u>	<u>-R</u>	
				Option resistor Special design: A: with ground choke	
				Design sequence	
Series: Electrical circuit, see specific catalog page					
Current rating: AC rms e.g. :03 amp					

DELTA PARTS NUMBERING SYSTEM

3-Phase Types

10

TD

S6

D

Current rating: AC rms
e.g.: 10 amp

- Series:**
- TD: used in "Δ" system
 - TDH: used in "Δ" system
 - TDR: used in "Δ" system, vertical style
 - TDV: used in "Δ" system, vertical style
 - TDS: used in "Δ" system, screw style
 - TY: used in both "Δ" & "y" system
 - TYS: used in "Δ" & "y" system, screw style
 - TYT: used in "Δ" & "y" system terminal block style
 - PT: P.C.B. Filter
 - PY: P.C.B. Filter

Input/Output connection :
 G = lugs; W = PVC wires; S = screws; T = terminal blocks
 e.g.
 G6 = 6 lugs
 W6 = 6 wires
 T2: 2 terminal blocks
 TIW4: 1 terminal block / 4 wires

Special Design:
 Dual: diff. and common choke

