

DELTA PARTS NUMBERING SYSTEM

MODELS OTHER THAN POWER ENTRY MODULE TYPES AND P.C. BOARD MOUNTING TYPES

<u>03</u>	<u>GE</u>	<u>E</u>	<u>G3</u>	<u>V</u>	<u>-R</u>

Option resistor

Design sequence:
 (for cylinder types, the 8th digit designates the outside diameter; S- \varnothing 38mm; M- \varnothing 43mm; L- \varnothing 50mm)

Input/Output connection:
 G = lugs; W = PVC wires; S = screws
 G5 = 5 lugs (6.3*0.8mm)
 W5 = 5 wires (UL 1015 AWG#18, 4" long)

Case style:
 A- Small mounting ears 90 degrees from terminal sides
 B- Triangle mounting ears 90 degrees from terminal sides
 C- Triangle mounting ears on terminal sides
 D- IEC connector with mounting screws
 E- IEC connector package
 F- Cylinder types
 G- Two-hole mounting bars, 90 degrees from terminal sides
 N- IEC connector with snap-in type

Series: Electrical circuit, see specific catalog pages

Current rating: AC rms
 e.g.: 03 amp

POWER ENTRY MODULE TYPES

<u>06</u>	<u>AR</u>	<u>2</u>	<u>D</u>

Special design:
 A- with ground choke
 D- with double pole power switch for models AB, AK, AR series

Module construction:
 1- IEC connector & fuse holder
 2- IEC connector, fuse holder and power switch
 3- IEC connector, fuse holder, power switch and voltage selector switch
 4- IEC connector, fuse holder & voltage selector switch
 5- For models other than CK, CR series; same construction as 4 but with voltage selector switch at front panel

Series: Electric circuit, see specific catalog pages

Current rating: AC rms
 e.g.: 06 amp

PCB MOUNTING TYPES

<u>03</u>	<u>ME</u>	<u>3</u>	<u>A</u>	<u>-R</u>

Option resistor

Special design:
 A: with ground choke

Design sequence

Series: Electrical circuit, see specific catalog page

Current rating: AC rms
 e.g. :03 amp

DELTA PARTS NUMBERING SYSTEM

3-Phase Types

10

TD

S6

D

Current rating: AC rms
e.g.: 10 amp

Series:

- TD: used in "Δ" system
- TDH: used in "Δ" system
- TDR: used in "Δ" system, vertical style
- TDV: used in "Δ" system, vertical style
- TDS: used in "Δ" system, screw style
- TY: used in both "Δ" & "y" system
- TYS: used in "Δ" & "y" system, screw style
- TYT: used in "Δ" & "y" system terminal block style
- PT: P.C.B. Filter
- PY: P.C.B. Filter

Input/Output connection :

- G = lugs; W = PVC wires; S = screws; T = terminal blocks
- e.g.
- G6 = 6 lugs
- W6 = 6 wires
- T2: 2 terminal blocks
- TIW4: 1 terminal block / 4 wires

Special Design:

Dual: diff. and common choke

