

## RSM 16RS 24VDC GEM.-

**Weidmüller Interface GmbH & Co. KG**


Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

### Product image



Similar to illustration

Relay bases (RSM) with common positive and negative to be connected to PLC or other type of controllers. The interfaces are made up of groups of 4, 8 or 16 RCL relays (12.7 mm) or RSS (6.1 mm). The connection to the controller can be set up using pluggable connectors or using direct cabling with IEC 60603-13 connectors. Wide range of options:

- 1 or 2 CO contacts with 16/8/6 A relays
- Voltages from 5 to 230 V
- Screw, tension clamp or PUSH IN connection
- Compatible with Weidmüller's solid-state relays

The range of relays provides galvanic isolation between input/output as well as between the adjacent contacts on the relays. This enables the various voltages in the controllers and those required by the various field elements to be safely adapted.

### General ordering data

Version	RSM-Series, Relay module, Number of contacts: 16, CO contact AgNi 90/10, Rated control voltage: 24 V DC, Continuous current: 6 A, Screw connection, Test button available: No
Order No.	<a href="#">1113761001</a>
Type	RSM 16RS 24VDC GEM.-
GTIN (EAN)	4032248047574
Qty.	1 pc(s).

**RSM 16RS 24VDC GEM.-****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	76 mm	Depth (inches)	2.992 inch
Height	87 mm	Height (inches)	3.425 inch
Width	285 mm	Width (inches)	11.22 inch
Net weight	580.43 g		

**Temperatures**

Storage temperature	-40 °C...60 °C	Operating temperature	-25 °C...50 °C
Humidity	40 °C / 93 % rel. humidity, no condensation		

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1, 4,4'- isopropylidenediphenol 80-05-7	SCIP	66e752f3-a24f-4fef-89c4- f29f52d01390
------------	--	------	--

**Rating data**

Mechanical service life	30 x 10 <sup>6</sup> switching cycles	Switch-on delay	< 8 ms
Switch-off delay	< 7 ms		

**Ratings data input**

Power rating	0.75 W
--------------	--------

**Classifications**

ETIM 6.0	EC001437	ETIM 7.0	EC001437
ETIM 8.0	EC001437	ECLASS 9.0	27-37-16-01
ECLASS 9.1	27-37-16-01	ECLASS 10.0	27-37-16-01
ECLASS 11.0	27-37-16-01	ECLASS 12.0	27-37-16-01

**Approvals**

Approvals



ROHS	Conform
------	---------

**Downloads**

Approval/Certificate/Document of Conformity	<a href="#">Declaration of Conformity</a>
Engineering Data	<a href="#">EPLAN, WSCAD</a>
Product Change Notification	<a href="#">20210819 Technical change to RS SERIES - Relay modules</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>

Creation date September 16, 2022 12:01:05 AM CEST

Catalogue status 09.09.2022 / We reserve the right to make technical changes.

2