


## HBT GAIN BLOCK MMIC AMPLIFIER, 7 - 15 GHz

### Typical Applications

The HMC3653LP3BE is ideal for:

- Point-to-Point Radios
- Point-to-Multipoint Radios
- VSAT
- LO Driver for HMC Mixers
- Military EW & ECM

### Functional Diagram



### Features

- High Output IP3: +28 dBm
- Single Positive Supply: +5V
- Low Noise Figure: 4.0 dB <sup>[1]</sup>
- 12 Lead 3x3 mm SMT Package: 9mm<sup>2</sup>

### General Description

The HMC3653LP3BE is a HBT Gain Block MMIC amplifier covering 7 GHz to 15 GHz and packaged in a 3x3 mm plastic QFN SMT package. This versatile amplifier can be used as a cascadable IF or RF gain stage in 50 Ohm applications. The HMC3653LP3BE delivers 15 dB gain, and +15 dBm output P1dB with only 4 dB noise figure.


### Electrical Specifications, $T_A = +25^\circ\text{C}$ , $V_{cc} = 5\text{V}$ , $V_{pd} = 5\text{V}$

| Parameter  | Min.  | Typ.  | Max. | Min.   | Typ.  | Max. | Min.    | Typ.  | Max. | Units   |
|--|-------|-------|------|--------|-------|------|---------|-------|------|---------|
| Frequency Range  | 7 - 9 |       |      | 9 - 14 |       |      | 14 - 15 |       |      | GHz     |
| Gain <sup>[1]</sup>  | 10.5  | 14    |      | 12     | 15    |      | 12      | 15    |      | dB      |
| Gain Variation Over Temperature  |       | 0.016 |      |        | 0.016 |      |         | 0.022 |      | dB / °C |
| Input Return Loss  |       | 14    |      |        | 15    |      |         | 11    |      | dB      |
| Output Return Loss   |       | 8     |      |        | 8     |      |         | 7     |      | dB      |
| Output Power for 1 dB Compression (P1dB) <sup>[1]</sup>                      | 13    | 16    |      | 12     | 15    |      | 10.5    | 13.5  |      | dBm     |
| Output Third Order Intercept (IP3)<br>(Pout = 0 dBm per tone, 1 MHz spacing) |       | 26    |      |        | 28    |      |         | 26    |      | dBm     |
| Noise Figure <sup>[1]</sup>  |       | 6     |      |        | 4     |      |         | 4     |      | dB      |
| I <sub>cc</sub> (V <sub>pd</sub> = 5V)                                       |       | 40    | 55   |        | 40    | 55   |         | 40    | 55   | mA      |
| I <sub>cc</sub> (V <sub>pd</sub> = 0V)                                       |       | 4     | 6    |        | 4     | 6    |         | 4     | 6    | mA      |


[1] Board loss subtracted out

**HBT GAIN BLOCK  
MMIC AMPLIFIER, 7 - 15 GHz**


**Gain & Return Loss**




**Gain vs. Temperature**




**Input Return Loss vs. Temperature**




**Output Return Loss vs. Temperature**



**Noise Figure vs. Temperature**




**P1dB vs. Temperature**




**HBT GAIN BLOCK  
MMIC AMPLIFIER, 7 - 15 GHz**


**Psat vs. Temperature**




**Output IP3 vs Temperature**




**Phase Noise @ Pin=0 dBm**




**Power Compression @ 8 GHz**



**Power Compression @ 11 GHz**




**Power Compression @ 14 GHz**



## HBT GAIN BLOCK MMIC AMPLIFIER, 7 - 15 GHz

### Reverse Isolation



### Absolute Maximum Ratings


|   |               |
|---|---------------|
| Drain Bias Voltage  | 6 Vdc         |
| RF Input Power (RFIN)   | +12 dBm       |
| Channel Temperature   | 150 °C        |
| Continuous P <sub>diss</sub> (T=85 °C)<br>(derate 7.87 mW/ °C Above +85 °C) | 512 mW        |
| Thermal Resistance<br>(channel to ground paddle)                            | 127 °C/W      |
| Storage Temperature   | -65 to 150 °C |
| Operating Temperature   | -40 to +85 °C |
| ESD Sensitivity (HBM)   | Class 1A      |



ELECTROSTATIC SENSITIVE DEVICE  
OBSERVE HANDLING PRECAUTIONS

## HBT GAIN BLOCK MMIC AMPLIFIER, 7 - 15 GHz

### Outline Drawing



12-Lead Lead Frame Chip Scale Package [LFCSP]  
3 mm × 3 mm Body and 0.85 mm Package Height  
(CP-12-10)

Dimensions shown in millimeters

### Package Information






| Part Number  | Package Body Material                              | Lead Finish   | MSL Rating [2] | Package Marking [1] |
|--------------|--|---------------|----------------|---------------------|
| HMC3653LP3BE | RoHS-compliant Low Stress Injection Molded Plastic | 100% matte Sn | MSL1           | H3653<br>XXXX       |

[1] 4-Digit lot number XXXX

[2] Max peak reflow temperature of 260 °C

## HBT GAIN BLOCK MMIC AMPLIFIER, 7 - 15 GHz

### Pin Descriptions

| Pid Number              | Function | Description   | Interface Schematic   |
|-------------------------|----------|---|---|
| 1, 3, 4, 5, 6, 7, 9, 11 | NC       | No connection necessary. These pins may be connected to RF/DC ground. Performance will not be affected. |   |
| 2                       | RFIN     | This pin is AC coupled and matched to 50 Ohms.  | RFIN   |
| 8                       | RFOUT    | This pin is AC coupled and matched to 50 Ohms.  |  RFOUT |
| 10                      | Vcc      | Power supply voltage for the amplifier  |       |
| 12                      | Vpd      | Power Control Pin for proper control bias   |      |
| GND Paddle              | GND      | Ground Paddle must be connected to RF/DC ground.  |      |

**HBT GAIN BLOCK  
MMIC AMPLIFIER, 7 - 15 GHz**

**Application Circuit**

