



Product: [1164B](#)

RGB Video, #26-3 Coax Stranded BC, CM

Product Description

RGB Video Coax, 3-26 AWG Stranded (7x34) Bare Copper Conductors, Foam PE Insulation, Duofoil® + 95% Tinned Copper Interlocked Braid, Inner PVC jackets, Overall PVC Jacket, CM

Technical Specifications

Product Overview

Suitable Applications:	RGB Projectors, LCD Projectors, Video Distribution, Component Video, Graphic Displays, Special Effects Editing, Animation, Video Post Production, Home Theater, Offices, Boardrooms, Auditoriums, Teleconferencing, Theaters
------------------------	--

Construction Details

RG Type:	Mini 59
----------	---------

Conductor

Element	No. of Elements	Size	Stranding	Nom. Diameter	Material
Coax(es)	3	26 AWG	7x34	0.019 in	BC - Bare Copper

Insulation

Material	Nom. Insulation Diameter	Color Code
PE - Polyethylene (Foam)	0.089 in (2.3 mm)	Red, Blue, Green

Inner Shield

Layer	Shield Type	Material	Material Trade Name	Coverage
1	Tape	Tri-Laminate (Alum+Poly+Alum)	Duofoil®	100%
2	Braid	Tinned Copper (TC)		95%

Inner Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.146 in (3.71 mm)

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.388 in (9.86 mm)

Electrical Characteristics

Return Loss (RL)

Frequency	Min. Return Loss
10-40 MHz	25 dB

Attenuation

Frequency	Nom. Attenuation
1 MHz	0.6 dB/100ft
5 MHz	1.3 dB/100ft
10 MHz	1.8 dB/100ft
30 MHz	3.1 dB/100ft
50 MHz	3.9 dB/100ft

100 MHz	5.4 dB/100ft
200 MHz	7.5 dB/100ft
400 MHz	10.4 dB/100ft
700 MHz	13.5 dB/100ft
900 MHz	15.2 dB/100ft
1000 MHz	15.9 dB/100ft

Electricals

Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
41.5 Ohm/1000ft	7.7 Ohm/1000ft (25 Ohm/km)	17.3 pF/ft (56.8 pF/m)	75 Ohm	78%

Voltage

UL Voltage Rating
300 V RMS, 300 V RMS (CM)

Electrical Characteristics Notes:	30 V RMS (UL AWM Style 1354), 300 V RMS (CM)
-----------------------------------	--

Mechanical Characteristics

Temperature

UL Temperature	Operating
60°C	-40°C To +60°C

Bend Radius

Stationary Min.	Installation Min.
3.88 in (98.6 mm)	3.88 in (98.6 mm)

Max. Pull Tension:	103 lbs (46.7 kg)
Bulk Cable Weight:	70 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Flammability / Reaction to Fire:	UL1685 UL Loading
NEC / UL Compliance:	Article 800, CM
AWM Compliance:	AWM 1354 (30 V 60°C) (each coax), AWM 2668 (overall)
CEC / C(UL) Compliance:	CM
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.439 Revision Date: 11-14-2023
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
1164B 010500	Black	Reel	500 ft	612825355052	C
1164B 0101000	Black	Reel	1,000 ft	612825355069	C

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.