



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to

Rosenberger P-SMP

**Documents**

Application note

AN001 "Calibration Services"

**Material and plating**

**Connector parts**

- Center conductor
- Outer conductor
- Dielectric

**Material**

- CuBe
- CuBe or equiv.
- PS

**Plating**

- Gold, min. 1.27 µm, over nickel
- Gold, min. 1.27 µm, over nickel

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/05.10/6.0

**Electrical data**

Frequency range	DC to 10 GHz
Return loss	≥ 30 dB, DC to 4 GHz ≥ 26 dB, 4 GHz to 10 GHz

**Mechanical data**

Mating cycles Plug side	≥ 100
Mating cycles Jack side	
- if mating part is Smooth bore	≥ 1000
- if mating part is Limited detent	≥ 500
- if mating part is Full detent	≥ 100
Engagement force	
- Smooth bore	10 N
- Limited detent	45 N
- Full detent	68 N
Disengagement force	
- Smooth bore	2.2 N
- Limited detent	15 N
- Full detent	25 N
Gauge	0.00 mm to 0.08 mm

**General standard definition**

For proper operation the vector network analyzer (VNA) needs a model describing the electrical behaviour of this calibration standard. The different models, units, and terms used will depend on the VNA type and they will have to be entered into the VNA. All values are based on typical geometry and plating.

Offset $Z_o$ / Impedance / $Z_o$	50 $\Omega$
Offset Delay	71.6899 ps
Length (electrical) / Offset Length	21.50 mm
Offset Loss	2.51 G $\Omega$ /s
Loss	0.0156 dB/ $\sqrt{\text{GHz}}$

**Environmental data**

Operating temperature range <sup>1</sup>	+20 °C to +26 °C
Rated temperature range of use <sup>2</sup>	0 °C to +50 °C
Storage temperature range	-40 °C to +85 °C

RoHS compliant

<sup>1</sup> Temperature range over which these specifications are valid.

<sup>2</sup> This range is underneath and above the operating temperature range, within the calibration adaptor is fully functional and could be used without damage.

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/05.10/6.0