REV.	DATE	DESCRIPTION
NC	01/28/03	INITIAL RELEASE



RECOMMENDED
CABLE STRIPPING DIM'S





NOTE:

1. CRIMPED CONTACT PIN
   HEX CRIMP SIZE .068"

	DESCRIPTION	MATERIAL	FINISH	QTY
8	CONTACT PIN	BRASS	GOLD	1
7	WASHER	BRASS	NICKEL	1
6	RING	DELRIN	NATURAL	1
5	RETAINER RING	BRASS	NICKEL	1
4	GASKET	RUBBER	RED	1
3	INSULATOR	TEFLON	NATURAL	1
2	BODY	BRASS	GOLD	1
1	SHELL	BRASS	NICKEL	1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS		DATE
DRAWN	G.R.S.	01/28/03
CHECKED		
ISSUED		
SHEET	1 OF 1	
CAD FILE	C:/122/122386HEX.DWG	

Amphenol Connex

PART DESCRIPTION
TNC DIRECT SOLDER PLUG
HEX COUPLING NUT (.141 SEMI RIGID CABLE)

PART NO. 122386HEX

DWG. NO.	REV.	SIZE	SCALE
122386HEX.DWG	NC	A	NA