


Position Sensors

Severe Environment Proximity Sensors

100FW Series



FEATURES

- All-metals sensitive
- Designed for aircraft, ordnance, marine, mass transit, high performance industrial equipment
- Stainless steel housing, thick wall construction for effective shielding
- Leadwire or connector termination
- Factory Mutual certified for Class I, Division 2, Groups A, B, C, D
- Circuit protection against:
 - Transients, MIL-STD-704
 - EMI, MIL-STD-461
 - False pulse
 - Load shorts
 - Reverse voltage
 - 400 Hz interference

100FW ORDER GUIDE

Sensor Package Style	Sensing Range mm (in.)	Repeatability, (max.)	Switching Frequency**	Standard Target* mm (in.)	Termination	Catalog Listing
5/8-24 UNEF	2,41mm ± 0,51 (.095 ± .02) Shielded	± 1%	500 Hz	15,9 dia. x 1,59mm (.625 dia. x .062) (SAE 1018 steel)	Connector	112FW12-R1
					Leadwire	112FW12-4
5/8-24 UNEF	5,84mm ± 0,76 (.230 ± .03) Unshielded	± 1%	500 Hz	15,9 dia. x 1,59mm (.625 dia. x .062) (SAE 1018 steel)	Connector	122FW12-R1
					Leadwire	122FW12-4


* For any given set of environmental conditions. Note: for most aerospace applications, repeatability is not specified; all variations, including repeatability, environmental effects and manufacturer's tolerances are included in the basic tolerance of operating parameters.

** Varies with application details (target size, distance, etc.); should be evaluated for each installation design.

MOUNTING DIMENSIONS

For reference only

mm
in.



ELECTRICAL SPECIFICATIONS

Supply Voltage (Vs)	18-32 VDC
Leakage Current	10 µA
Voltage Drop, max.	1.0 V
Current Consumption, max. (exclusive of load)	20 mA
Load Current, max.	120 mA, 50 mA Lamp
Hysteresis	0,13mm (.005)
Circuit Protection	Transients, MIL-STD-704 False pulse Load shorts EMI, MIL-STD-416A Reverse voltage 400 Hz interference

4551830 0018703 T89