

IE-SFP-1GLHXLC**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image

- Supports DDM (Digital Diagnostic Monitoring)
- IEEE 802.3z compliant (Gigabit Ethernet SFPs)
- IEEE 802.3u compliant (Fast Ethernet SFPs)
- Symmetric LVPECL I/Os (Gigabit Ethernet SFPs)
- Symmetric PECL I/Os (Fast Ethernet SFPs)
- TTL signal detection indicator
- Pluggable in operation (hot pluggable)
- Class 1 laser product, EN60825-1 compliant
- Applicable for switches of the Basic-, Value- and PremiumLine

General ordering data

Version	SFP Transceiver, 1000 Mbps, Singlemode, LC-Duplex, 40 km, 0 °C...60 °C
Order No.	1241520000
Type	IE-SFP-1GLHXLC
GTIN (EAN)	4050118029369
Qty.	1 pc(s).

Creation date September 16, 2022 2:47:18 AM CEST

Catalogue status 09.09.2022 / We reserve the right to make technical changes.

IE-SFP-1GLHXLC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 36 g

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	0 °C...60 °C
Humidity	5 to 95 % (non-condensing)		

EMC conformity and approvals

EMC standards	EN 55032, EN 55024	Safety standard	UL 60950-1
Ship use	DNV-GL		

Environmental conditions

Humidity	5 to 95 % (non-condensing)	Operating temperature, max.	60 °C
Operating temperature, min.	0 °C	Storage temperature, max.	85 °C
Storage temperature, min.	-40 °C		

Fibre optic transceiver characteristics

Transmission rate	1000 Mbps														
Digital diagnostic monitor function (DDM)	Supported														
Transceiver type	Singlemode														
Connector type	LC-Duplex														
Transmission distance, typ.	40 km														
Wavelength	<table> <tr> <td>typ.</td> <td>1,310 nm</td> </tr> <tr> <td>Wavelength</td> <td>TX</td> </tr> <tr> <td>min.</td> <td>1,280 nm</td> </tr> <tr> <td>max.</td> <td>1,340 nm</td> </tr> <tr> <td>Wavelength</td> <td>RX</td> </tr> <tr> <td>min.</td> <td>1,260 nm</td> </tr> <tr> <td>max.</td> <td>1,610 nm</td> </tr> </table>	typ.	1,310 nm	Wavelength	TX	min.	1,280 nm	max.	1,340 nm	Wavelength	RX	min.	1,260 nm	max.	1,610 nm
typ.	1,310 nm														
Wavelength	TX														
min.	1,280 nm														
max.	1,340 nm														
Wavelength	RX														
min.	1,260 nm														
max.	1,610 nm														
Receive power	<table> <tr> <td>min.</td> <td>-24 dBm</td> </tr> <tr> <td>max.</td> <td>-1 dBm</td> </tr> </table>	min.	-24 dBm	max.	-1 dBm										
min.	-24 dBm														
max.	-1 dBm														
Transmission power	<table> <tr> <td>min.</td> <td>-4 dBm</td> </tr> <tr> <td>max.</td> <td>3 dBm</td> </tr> </table>	min.	-4 dBm	max.	3 dBm										
min.	-4 dBm														
max.	3 dBm														
Link-budget	20 dB														

Guarantee

Time interval 3 years

Power supply

Voltage supply 3.3 V (via Ethernet switch)

Technical data

Type of mounting Insert in SFP slot