

NOTES:

1. FOR USE WITH BOEING BMS13-65 OG & ADAMS RUSSELL FC20Z CABLE.
2. FOR CABLING INSTRUCTIONS SEE 3-546-1.
3. FOR CRIMPING USE DIE KTH-2216.
4. INTERFACE PER MIL-STD-348, FIG. 313-1.
5. CENTER CONTACT (1-504-46MAG) SUPPLIED UNASSEMBLED.
6. MARK PACKAGE: KINGS 126-71-9 YRWK (DATE/LOCATION CODE)
7. MATERIALS:
 INSULATORS: TEFLON, ASTM-D-1710
 GASKET: SILICONE RUBBER, A-A-59588
 G-RING: PHOSPHOR BRONZE, ASTM-B103
 K-GRIP SLEEVE: COM. BRONZE, ASTM-B135
 OUTER CONTACT } BER. COPPER, ASTM-B196
 CENTER CONTACT F }
 ALL OTHER METAL PARTS: BRASS, ASTM-B16

8. FINISHES:

- CENTER CONTACTS: .000050 MIN GOLD PER ASTM B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290(ROHS)
- OUTER CONTACT: .000200 MIN SILVER PER ASTM B700 OVER .000020 MIN. COPPER PER ASTM B734(ROHS)
- ALL OTHER METAL PARTS: .000050 MIN NICKEL PLATE PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734(ROHS)

9. ELECTRICAL CHARACTERISTICS:

- NOMINAL IMPEDANCE: 50 OHMS
- WORKING VOLTAGE: 500 VRMS
- FREQUENCY RANGE: DC TO 11 GHz.
- VSWR: 1.30 MAX. 5-11 GHz.
- INSERTION LOSS: DC TO 1.5 GHz, 0.045 DB MAX
- 1.5 TO 5.0 GHz, 0.085 DB MAX
- 10. WEIGHT: 36.78 GRAMS (0.081 POUNDS)

UNLESS OTHERWISE SPECIFIED
 1. ALL DIMENSIONS IN INCHES [MILLIMETERS].
 2. TOLERANCES:
 .XXX ±.004
 .XX ±.010
 [.XXX ±.10] [.XX ±.25]
 FRACTIONS: X/Y ±.010 [.25]

★ CRITICAL DIMENSIONS ANGLES: ± 1°

126-71-9

REVISIONS	
ISSUE	CHANGES
E	ER 8354 RMS 05/29/08
F	ER 33785 COL 07/15/11


SALES DRAWING

THIS DRAWING, THE DESIGN AND IDEAS EMBODIED IN THE DRAWING TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1
 APPROX SURFACE AREA
 USED ON
 CAGE CODE:918336

PLUG, ANGLE, TNC

DRAWN KH	DATE 03/15/94
DESIGN JT	DATE 03/16/94
APPR.	DATE



126-71-9

SIZE B