

1300 Series MMCX

50 Ohm Cable and PCB Connectors



Bomar products, like the 1300 Series MMCX 50 Ohm Cable and PCB Connectors, are now sold under the Win™ brand from Winchester Interconnect™.

Product Description

Winchester Interconnect's 1300 Series 50 Ohm MMCX Connectors are 30% smaller than MCX Connectors.

Due to their small size, MMCX Connectors can be used in a wide range of applications including Test and Measurement, Mil-Aero, Satellite Communication, Wireless Communication, and Medical Equipment.

Our 1300 Series 50 Ohm MMCX Connectors are designed in accordance with European Specification CECC 22000 and feature a "Snap-On" interface designed for a frequency range of DC to 6 GHz.

Male cable plug connectors are available in straight and right-angle designs for popular flexible and semi-rigid cables.

Printed circuit board (PCB) connectors are available in straight and right-angle through-hole solder and also in our unique E-Snap® Edge-Mount design.



- Quick connect disconnect snap-on mating reduces installation time.

- Due to their miniature size, MMCX Connectors are ideal for high density applications requiring a very small RF interconnect.

 **Winchester**
Interconnect.

We Energize Innovation.


Specifications

<p>Electrical Impedance 50 Ohms</p> <p>Frequency DC to 6 GHz</p> <p>RF-Leakage 60 dB Min at 1 GHz</p> <p>Dielectric Withstanding Voltage 500 VRMS at sea level</p> <p>VSWR <i>Straight</i> 1.15 Max DC – 4 GHz <i>Right-Angle</i> 1.4 Max 4 – 6 GHz</p>	<p>Contact Resistance Center ≤ 10 Megohms Outer ≤ 5 Megohms</p> <p>Insulation Resistance 1000 Megohms Min</p> <p>Mechanical Mating Snap-On Coupling</p> <p>Contact Captivation 2.3 lbs.</p>	<p>Engagement Force ≤ 3.4 lbs. (15N)</p> <p>Disengagement Force ≥ 1.4 lbs. (6N)</p> <p>Durability 500 Cycles Min</p> <p>Material Body Brass</p> <p>Body Finish Nickel</p> <p>Contact Male Brass Female BECU</p>	<p>Contact Finish Gold</p> <p>Insulator PTFE</p> <p>Crimp Ferrule Copper or Brass Nickel Plated</p> <p>Environmental Temperature Range -55°C to +155°C</p> <p>Thermal Shock MIL-STD-202, Method 107</p>	<p>Moisture Resistance MIL-STS-202, Method 105</p> <p>Corrosion MIL-STD-202, Method 101</p> <p>Mechanical Shock MIL-STD-202, Method 101</p> <p>Humidity MIL-STD-202, Method 101</p>
--	---	---	--	---

Part Numbers

Part Number	Straight and Right-Angle Cable Plugs	Crimp Tool	Hex Size
1310A204F	Straight Cable Plug for RG178, RG196	BDHD200	Solder / 0.128
1310A204M	Straight Cable Plug for RG174, RG316, LMR100	BDHD200	Solder / 0.128
1310A204S	Straight Cable Plug for RD316	BDHD200	Solder / 0.151
1320A204-405	Straight Cable Plug for RG405 Semi-Rigid	Solder	Solder
1320A204-047	Right-Angle Cable Plug for 0.047 Semi-Rigid	Solder	Solder
1313A204F	Right-Angle Cable Plug for RG178, RG196	BDHD200	Solder / 0.128
1313A204M	Right-Angle Cable Plug for RG174, RG316, LMR100	BDHD200	Solder / 0.128
1313A20MS	Right-Angle Cable Plug for RD316	BDHD200	Solder / 0.151
1313A204-405	Right-Angle Cable Plug for RG405	Solder	Solder
1313A204-047	Right-Angle Cable Plug for 0.047 Semi-Rigid	Solder	Solder

Part Number	Printed Circuit Board Connectors	PCB Thickness	Packaging
1362A514	Vertical, MMCX, Plug, 0.155" Solder Tail	0.062"	Single
1361A514	Vertical, MMCX, Jack, 0.155" Solder Tail	0.062"	Single
1361E514	Edge-Mount, MMCX, Jack	0.062"	Single
1364A514	Right-Angle, MMCX, Jack, 0.155" Solder Tail	0.062"	Single
1361E504	E-Snap® Edge-Mount, MMCX, Jack	0.062"	Single

Win  Bomar products are now under the Win™ brand from Winchester Interconnect.