Data Sheet

SENCITY® Road MULTI Antenna 1399.19.0416

Description

Rugged vehicle rooftop multi-band antenna for commercial vehicles like bus and truck. Supports Wifi 2.4/5 GHz, Wifi 6E. 6 separate ports for 6x6 Wifi MIMO. Meets ISO16750 automotive standard. Fire retardant acc. to ECE-R118. Single hole mounting, easy cabling feed-through.

Product Configuration

Technical Data Electrical Data Band 1 Band 2 Band Name WiFi WiFi 2400 - 2500 4900 - 7125 Frequency (MHz) VSWR 2 2 50 Impedance (Ohm) 50 Gain (dBi) 6 6 Composite power max (W) 30 30 25 Ambient temperature (°C) 25 Port isolation (dB) 24 24

Ports

		Port 1 to 6	
Port name		WiFi 1-6 (blue)	
Connector		SMA, plug (male)	
Cable Type		ENVIROFLEX_316_D-AM	
Cable Length (m)		0.3	
Polarization		Vertical	
DC Grounded		Yes	
Connection	າຣ		
	Band 1	Band 2	
Port 1 to 6	х	X	

HUBER+SUHNER

Data Sheet

HUBER+SUHNER

SENCITY® Road MULTI Antenna 1399.19.0416

General Data

Ground plane: Indicated VSWR values are valid for a metallic ground plane of 0.5 x 0.5m or larger and Isolation is provided as typical values. Indicated VSWR values are mostly valid for installations on non-metallic surfaces also (no specific ground plane requirements). Indicated gain values will be achieved on a metallic ground plane of 1 x 1 m or larger.

Mechanical Data

Dimensions (mm)	210 x 60 (Diameter x Hei		
Weight (kg)	1.1		
Mounting breakthrough	Ø30mm		

Environmental Data

Environmental conditions Operation temperature (°C) Storage temperature (°C) Transport temperature (°C) IP rating Flammability rating Solar radiation 2011/65/EU (RoHS - including 2015/863 and 2017/2102) REACH 1907/2006/EC

Environmental tests: ISO 16750:2012/2010 Low corrosion designed acc. to MIL-F-14072D E-Mark CE-Mark

Material Data

Radome colour Radome material Back plate/base plate material

Related Products

(Order separately) 9091.99.0250 Metal ground plane foil 0.6x0.6m

Related Documents

Mounting instruction Painting instruction Security instruction Outline drawing 3D-model

eight)

outdoor -40 to 85

-40 to 85

-40 to 85

IP68, IP69k ECE-R118 DIN 75220

compliant

compliant

RAL 7043 (dark grey) PC (Polycarbonate) Aluminium

DOC-0001163417 DOC-0000256180 DOC-0000278984 DOU-01159002 DOC-0001155892

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, AS/EN9100, ISO/TS 16949 and IRIS.

www.hubersuhner.com

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.