CABLE + SEAL (OD) UNSEALED (OD1)	WIRE SIZE AWG	WIRE SIZE METRIC	WIRE SIZE (METRIC)	CONDUCTOR CRIMP HEIGHT (SECT C-C) (+/-0.03)	CONDUCTOR CRIMP HEIGHT METRIC (SECT C-C) (+/-0.8)	CONDUCTOR CRIMP WIDTH (SECT C-C) (+/-0.10)	INSULATION CRIMP HEIGHT (SECT D-D) (+/-0.03)	INSULATION CRIMP HEIGHT METRIC (SECT D-D) (+/-0.8)	INSULATION CRIMP WIDTH (SECT D-D) (+/-0.10)	INSULATION CRIMP PUNCH OPTION	INSUL GRIP FORM TYPE SECT-D
US 22		0.35		1.40	1.30	2.05	1.95	1.95	2.60		2
CS 18		0.75/1.00		1.50	1.30/1.50		4.20+	4.15/4.20+		4.10+	2
CS 20		0.50		1.30	1.25	2.45	4.05+	4.05			2
US 18		0.75/1.00		1.50	1.30/1.50		2.35	2.35/2.45	2.80		2
US 20		0.50		1.30	1.25		2.20	2.20	2.55	OPTION 2	2
CS 14		2.00/2.50		1.95	1.75/1.80	3.05	5.00+	4.80/5.00+	5.20+		2
CS 16		1.50		1.80	1.70		4.50/3.5+	4.50+			2
US 14		2.00/2.50		1.95	1.75/1.80		3.25	3.10+/3.25	3.60		2
US 16		1.50		1.80	1.70		2.90	3.00			2
US 21(8-0.5)		21(.8-0.5)		1.90-1.60+	1.90-1.60+	3.25	3.7-2.3+	3.7-2.3+	4.30+	OPTION 1	1
CS N/A		2.5		N/A	1.80	3.45	N/A	5.00	5.20		2
US N/A		2.5					N/A	N/A	N/A	OPTION 2	2
CS 10		5.00/6.00		2.45	2.40+/2.50+		5.75+	5.75/5.9+			2
CS 12		4.00		2.20	2.05	3.85	5.30+	5.50+	5.80+		2
US 10		5.00/6.00		2.45	2.40+/2.50+		3.70	4.30		OPTION 1	1
US 12		4.00		2.20	2.30		SEE US 10 DIMENSIONS	4.20	4.35		1

* NOT VERIFIED TO USCAR-21

CRIMP WIDTH	CORE/ INSULATION	INSULATION CRIMP OPTION	E (+0.03/-0.03)	F (+0.03/-0.03)	G (+0.03/-0.03)	J (+0.03/-0.03)	K (+0.03/-0.03)	M (+0.03/-0.03) ANVILS	W (+0.03/-0.03)	N (+0.03/-0.03)	P (+0.03/-0.03)	R (+0.03/-0.03)	S (+0.03/-0.03)	T (+0.03/-0.03)	U (+0.03/-0.03)
2.05	CONDUCTOR	---	0.92	0.53	0.12	2.56	1.99	---	1.97	---	---	---	---	---	---
2.45	CONDUCTOR	---	1.09	0.63	0.16	3.06	2.38	---	2.36	---	---	---	---	---	---
2.60	INSULATION	2	---	---	---	---	---	0.60	---	0.16	3.25	2.53	2.50	N/A	N/A
2.80	INSULATION	2	---	---	---	---	---	0.60	---	0.18	3.50	2.72	2.69	N/A	N/A
3.05	CONDUCTOR	---	1.36	0.78	0.22	3.81	2.96	---	---	---	---	---	---	---	---
3.25	CONDUCTOR	---	1.45	0.84	0.22	4.06	3.12	---	---	---	---	---	---	---	---
3.45	CONDUCTOR	---	1.54	0.89	0.24	4.31	3.35	3.32	---	---	---	---	---	---	---
3.60	INSULATION	2	---	---	---	---	---	0.60	---	0.25	4.58	3.50	3.46	N/A	N/A
3.85	CONDUCTOR	---	1.72	0.99	0.28	4.81	3.70	---	---	---	---	---	---	---	---
4.10	INSULATION	2	---	---	---	---	---	0.60	---	0.30	5.12	3.98	3.94	N/A	N/A
4.30	INSULATION	1	---	---	---	---	---	0.60	---	0.32	5.38	4.17	4.13	1.92	1.11
4.35	INSULATION	1	---	---	---	---	---	1.10	---	0.38	5.18	4.70	4.64	---	---
5.20	INSULATION	2	---	---	---	---	---	1.00	---	0.40	5.50	5.00	4.94	---	---
5.80	INSULATION	2	---	---	---	---	---	1.00	---	0.47	6.18	5.60	5.52	---	---

CRIMP TOOL INFORMATION (REF. ONLY)

| | | | | |