USED IN ASSEMBLY	MATING CONFIG	MATING NON-DELPHI	MATING DELPHI	PREVIOUS PART
	DETAIL	PART NUMBER	PART NUMBER	NUMBER
-	-	-	15544901	•

ASSOCIATED PARTS					
PART	NUMBER	QTY	DE	SCRIP	TION
1 36	67839	1	COV	WIRE	<b>DRESS</b>
1 36	67840	1	COV	WIRE	DRESS
155	45822	1	COV	WIRE	DRESS
155	45824	1	COV	WIRE	DRESS

CAVITY INFORMATION					
CAVITY NAME	TERMINAL	CABLE SEAL	CAVITY PLUG	*INSULATION CRIMP HEIGHT	*INSULATION CRIMP WIDTH
A,C,F,H,J-N,P,R- X	13663715	-	1 3756464	4.0	4.0
B,D,E,G	13783267	-	1 3756465	4.2	4.2

## NOTES

- ICH AND ICW REPRESENT DIAMETRIC VALUES
- ASSEMBLIES MEET PRESSURE/VACUUM LEAK SUBMERGED IN WATER OF GREATER THAN 7 PSI AFTER THERMAL CONDITIONING.
- ASSEMBLY NUT TORQUE TO BE 2.5 TO 3.5 NM.

## DELPHI

DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE WARREN, OH

COPYRIGHT 2013 DELPHI CORPORATION AND/OR ITS AFFILIATES. ALL RIGHTS RESERVED.

THIS DRAWING IS THE PROPERTY OF DELPHI CORPORATION.
THE REPRODUCTION, DISTRIBUTION AND UTILIZATION
OF THIS DOCUMENT OR ITS RELATED CAD MATH DATA,
AS WELL AS COMMUNICATION OF ANY CONTENT TO OTHERS,
WITHOUT EXPRESS AUTHORIZATION IS PROPULIFIED. WITHOUT EXPRESS AUTHORIZATION IS PROHIBITED.

	DATE			
APVDI IVAN MACIAS	05JN13			
APVD2 G. ROBISON	06JN13			
PUBLISHED DATE 26FF15				

DRAWING NAME

ASM CONN 21 M HES 1.6 2.4 SLD MODULAR

DRAWING NUMBER

A LINE DRAWN THROUGH A PART NUMBER
INDICATES THAT PHYSICAL PARTS ARE NOT AVAILABLE FOR ORDERING.

PART NUMBERS THAT DO NOT HAVE A LINE PRESENT INDICATE THAT PHYSICAL PARTS ARE AVAILABLE FOR ORDERING.

CONTACT DELPHI SALES TO ASSURE AVAILABILITY OF PARTS.

## APPLICATION DRAWING

UNLESS OTHERWISE SPECIFIED

WHEN APPLICABLE, EQUIVALENT PART NUMBERS MAY BE SUBSTITUTED FOR ANY OF THE PART NUMBERS SHOWN IN THE CHARTS ON THIS DRAWING.

\* THE VALUES REPRESENT THE CAVITY CAPABILITIES. THE ACTUAL TERMINAL CRIMP DIMENSIONS MUST BE LESS THAN THE VALUES SHOWN.