


NOTES:

1. INTERFACE PER MIL-STD-348, FIG. 314-1.
2. MATERIALS:  
INSULATOR: TEFLON, ASTM-D1710  
ALL OTHER METAL PARTS: BRASS, ASTM B16
3. FINISHES:  
CENTER CONTACT: .000100 MIN GOLD PER ASTM B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290.  
ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734.
4. ELECTRICAL CHARACTERISTICS:  
NOMINAL IMPEDANCE: NON-CONSTANT  
VOLTAGE RATING: 3500 VRMS  
5000 VDC

SD1709-5

REVISIONS	
ISSUE	CHANGES
3	CN 34186 C REDRAWN KH 11/06/92
E	UPDATED TO DMF304 PER ERO47669 BSS 5/13/13
CUSTOMER SALES DRAWING	
THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.	
SCALE 4:1	
APPROX SURFACE AREA	
USED ON	
REF:	
ADAPTER, M-M, SHV	
DRAWN KH	DATE 11/09/92
DESIGN LI	DATE 11/10/92
APPR.	DATE
 Winchester Electronics Corporation 199 Park Road Ext Suite 104 Middlebury, Connecticut 06762	
SD1709-5	