



1965-3-9 S.D

REVISIONS	
ISSUE	CHANGES
0	ER 10818 NLA 24 FEB 72
1	CN 15918A GA 15 JUL 76
2	CN 25083 C SL 1 SEP 83
3	CN 34639 C KH 17 MAY 93
4	CN 35740 A KH 12 AUG 94

NOTES.
 1. FOR USE WITH BELDEN 5422 CABLE.
 2. SAME AS 1965-3 EXCEPT FOR FINISH.
 3. FOR CABLING INSTRUCTIONS SEE C-59-315-1.

17	1	INSULATOR	C-59-187-4-M99
16	1	BAYONET SLEEVE	
15	1	INSULATOR	C-59-187-3-M99
14	1	OUTER CONTACT	C-59-187-2-M99
13	1	BNC CONTACT M	1-4896-3MA9
12	1	GASKET	
11	1	SPRING WASHER	
10	1	CAM LEVER	
7	1	INSULATOR	C-59-187-5-M99
6	1	RETAINER	1-1119-1M06
5	1	BRAID CLAMP	631-5-M06
4	1	GASKET	631-6-M99
3	1	WASHER	260C-1-M06
2	1	BODY	C-59-166-6-M06
1	1	CLAMP NUT	631-4-M06

S-D

FINISH
SPEC. KER 10004

MATL.
SPEC.

BNC TRIAX PLUG

DRAWN NLA DATE 23 FEB 72
 APPR. J.M. DATE 24 FEB 72

KINGS ELECTRONICS
 40 HANBLEDALE ROAD
 TUCKAHOE, N. Y.

1965-3-9 S.D.

UNLESS OTHERWISE SPECIFIED:

- | | |
|--|--|
| <p>1. TOLERANCES:
 FRACTIONS ± .010 DECIMALS ± .004 ANGLES ± 0° 30'
 T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED THE SUM OF THEIR TOLERANCES.</p> | <p>2. REMOVE ALL BURRS. BREAK SHARP EDGES .003 MAX.
 3. NO FILLETS PERMITTED.
 4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX.
 5. ALL DIMENSIONS PRIOR TO PLATING.</p> |
|--|--|

DIETZGEN 1968 General Training Yellows E307