

DELTA PARTS NUMBERING SYSTEM

MODELS OTHER THAN POWER ENTRY MODULE TYPES AND P.C. BOARD MOUNTING TYPES

| | | | | | |
|--|-----------|----------|-----------|----------|---|
| <u>03</u> | <u>GE</u> | <u>E</u> | <u>G3</u> | <u>V</u> | <u>-R</u> |
| | | | | | |
| | | | | | Option resistor Design sequence: (for cylinder types, the 8th digit designates the outside diameter; S- \varnothing 38mm; M- \varnothing 43mm; L- \varnothing 50mm) |
| | | | | | Input/Output connection: G = lugs; W = PVC wires; S = screws G5 = 5 lugs (6.3*0.8mm) W5 = 5 wires (UL 1015 AWG#18, 4" long) |
| | | | | | Case style: A- Small mounting ears 90 degrees from terminal sides B- Triangle mounting ears 90 degrees from terminal sides C- Triangle mounting ears on terminal sides D- IEC connector with mounting screws E- IEC connector package F- Cylinder types G- Two-hole mounting bars, 90 degrees from terminal sides N- IEC connector with snap-in type |
| Series: Electrical circuit, see specific catalog pages | | | | | |
| Current rating: AC rms e.g.: 03 amp | | | | | |

POWER ENTRY MODULE TYPES

| | | | | | |
|--|-----------|----------|----------|---|--|
| <u>06</u> | <u>AR</u> | <u>2</u> | <u>D</u> | | |
| | | | | | |
| | | | | Special design: A- with ground choke D- with double pole power switch for models AB, AK, AR series | |
| | | | | Module construction: 1- IEC connector & fuse holder 2- IEC connector, fuse holder and power switch 3- IEC connector, fuse holder, power switch and voltage selector switch 4- IEC connector, fuse holder & voltage selector switch 5- For models other than CK, CR series; same construction as 4 but with voltage selector switch at front panel | |
| Series: Electric circuit, see specific catalog pages | | | | | |
| Current rating: AC rms e.g.: 06 amp | | | | | |

PCB MOUNTING TYPES

| | | | | | |
|---|-----------|----------|----------|---|--|
| <u>03</u> | <u>ME</u> | <u>3</u> | <u>A</u> | <u>-R</u> | |
| | | | | | |
| | | | | Option resistor Special design: A: with ground choke | |
| | | | | Design sequence | |
| Series: Electrical circuit, see specific catalog page | | | | | |
| Current rating: AC rms e.g. :03 amp | | | | | |

DELTA PARTS NUMBERING SYSTEM

3-Phase Types

10

TD

S6

D

Current rating: AC rms
e.g.: 10 amp

Series:

- TD: used in "Δ" system
- TDH: used in "Δ" system
- TDR: used in "Δ" system, vertical style
- TDV: used in "Δ" system, vertical style
- TDS: used in "Δ" system, screw style
- TY: used in both "Δ" & "y" system
- TYS: used in "Δ" & "y" system, screw style
- TYT: used in "Δ" & "y" system terminal block style
- PT: P.C.B. Filter
- PY: P.C.B. Filter

Input/Output connection :

- G = lugs; W = PVC wires; S = screws; T = terminal blocks
- e.g.
- G6 = 6 lugs
- W6 = 6 wires
- T2: 2 terminal blocks
- TIW4: 1 terminal block / 4 wires

Special Design:

Dual: diff. and common choke

