



- △ BODY-MATL: BRASS PER MIL-C-50.
 FINISH: PLATED GOLD .000030 THK PER MIL-G-45204 FOR A LENGTH OF .200 MIN FROM MATING END, .000100 MIN TIN-LEAD PER MIL-T-10727 IN WIRE BARREL AREA, BOTH OVER NICKEL .000050 THK PER QQ-N-290.
 SPRING-MATL: STAINLESS STEEL PER QQ-S-766.
 POST-MATL: BRASS PER ASTM-B-134.
 FINISH: PLATED MATTE TIN-LEAD PER MIL-T-10727 OVER NICKEL .000050 THK PER QQ-N-290.
- △ BODY-MATL: BRASS PER MIL-C-50.
 FINISH: PLATED GOLD .000030 THK PER MIL-G-45204 FOR A LENGTH OF .200 MIN FROM MATING END, .000100 MIN TIN PER MIL-T-10727 IN WIRE BARREL AREA, BOTH OVER NICKEL .000050 THK PER QQ-N-290.
 SPRING-MATL: STAINLESS STEEL PER QQ-S-766.
 POST-MATL: BRASS PER ASTM-B-134.
 FINISH: PLATED MATTE TIN PER MIL-T-10727 OVER NICKEL .000050 THK PER QQ-N-290.

△	213289-2
△	213289-1
CONTACT FINISH	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DNW M. HOFFECKER 5-12-86	Tyco Electronics Corporation Harrisburg, Pa 17105-3608
DIMENSIONS: INCHES		CHK L. LAWVER 5-12-86	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	NAME
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± .010 ANGLES ± -		PRODUCT SPEC	CONNECTOR ASSEMBLY, PIN, 34 POSITION, RIGHT ANGLE, M SERIES
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS	RESTRICTED TO
CUSTOMER DRAWING		SCALE 2:1	SHEET 1 OF 1 REV L