



DO NOT SCALE  
DIMENSIONS IN mm

METRIC



P.C.B. HOLE DIM. ACTION PIN	
DRILLED HOLE	1,15 ±0,025 mm
FIN. HOLE	0,94 to 1,09 mm
AFTER REFLOW	0,91 to 1,09 mm
Cu-inks	0,025 to 0,075 mm
SnPb-inks	0,004 to 0,010 mm



ROW c	XX
ROW b	XX
ROW a	XX
POS	32 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1

AN ASTERISK „X” DENOTES A CONTACT.

NOTES:



MATERIAL:

- HOUSING: THERMOPL.POLYESTER  
COLOUR : GREY
- CONTACTS: PHOSPHORBRONZE



PLATING CONTACT :

- 1 : AT CONNECTOR MATING SIDE Au OVER Ni, PERFORMANCE LEVEL I, ACC. IEC 603-2. Sn AT ACTION-PIN.
- 4 : AT CONNECTOR MATING SIDE Au OVER Ni, PERFORMANCE LEVEL II, ACC. IEC 603-2. Sn AT ACTION-PIN.

REFERENCE FAMILY DRAWING 650473  
FOR ALL TYPE C HEADER OFFERINGS

OBSOLETE	SEE NOTE	SEE NOTE	218432-8
OBSOLETE	SEE NOTE	SEE NOTE	218432-7
	SEE NOTE	SEE NOTE	216432-4
	SEE NOTE	SEE NOTE	216432-1

				FINISH	MATERIAL	PARTNUMBER
-	-	-	-	-	-	-
E	REVISED PER ECO-20-009690	SY	HL	03NOV2020	CUSTOMER DRAWING FOR REFERENCE ONLY WILL NOT BE UPDATED	
D	REVISED PER ECO-15-006790	AP	RP	06MAY15	© COPYRIGHT 19 - BY Tyco Electronics EC N.V. ALL INTERNATIONAL RIGHTS RESERVED. Tyco PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING. THIS DRAWING IS UNPUBLISHED RELEASED FOR PUBLICATION .19	
C	SR10-0227-02	BC	BC	06-Apr-02	<b>STE</b> TE Connectivity	
B	EH-0831-97	J.G.	J.G.	28-07-97	NAME 64 POS. DIN 41612	
A	H-8830	R.v.L	J.v.G	29.07.91	TYPE C MALE CONN. WITH ACTION-PIN FOR 1,6 P.C.B. THK'S	
LTR.	REVISION RECORD	DR.	CHK.	DATE		
DR.:	Colpaert B.	CHK.:	Colpaert B.	APP.:	Colpaert B.	DWG.No.
DATE:	-	DATE:	-	DATE:	-	C- 216432
						REV.LTR. SHEET
						E 10F 1