LUMAWISE ENDURANCE N+

ANSI C136 COMPLIANT NETWORK LIGHTING CONTROLS:

PROTECTION FROM HARSH CONDITIONS

TE Connectivity (TE) LUMAWISE Endurance N+ network lighting control accessories include an ANSI C136 compliant base assembly with an integral seal gasket. The base assembly provides a power and signal interface solution between the network lighting control and luminaire mounted receptacle. Covers complete the enclosure. The base assembly with cover provide an IP66 rated control enclosure that protects from outdoor harsh environments, including rain, snow and salt spray.



THE BASE ASSEMBLY INCLUDES POWER TWIST LOCK TERMINALS, SPRING LEAF SIGNAL TERMINALS, AND AN INTEGRAL SEALING GASKET. COUPLE THAT WITH AN IKO8 RATED COVER AND THE ASSEMBLED NETWORK LIGHTING CONTROL ACHIEVES AN IP66 SEAL RATING.

FEATURES:

- ANSI C136.10/C136.41 compliant
- Achieve long term reliability using TE's power and signal interface
- Translucent covers allow transmission of daylight to the light sensing device
- Achieve protection against dust and heavy jet spray with an IP66 rated solution
- Incorporating a vent into the base assembly enables increased life expectancy of the electronics inside the enclosure

APPLICATIONS:

- Lighting controls
- · Street and area lighting
- · Roadway lighting
- Commercial outdoor lighting (i.e. parking lots, car dealerships)

CONTROL BASE AND COVER

MECHANICAL:

•5 position:

• Operating temperature range: -40°C to +105° C

• Offer 3, 5 and 7 position version

•3 position: 3 power contacts

3 power contacts + 2 dimming/signal contacts

•7 position: 3 power contacts +

4 dimming/signal contacts

• IK08 impact rating (Cover)

MATERIALS:

• Contact plating: Tin plated power contacts

Gold plated signal contacts

• Housing color: Base (black)

Cover (clear and transparent)

• Housing material: Base (UL 94 V-0)

Cover (Polycarbonate)

SPECIFICATIONS

Product: 108-32606Application: 114-32363

Product Selection Information

| | | Part number | Description | Position |
|-------|--|-------------|------------------------------|----------|
| | | 2359482-1 | 84.7mm Base assembly, w/vent | 7 |
| | | 2359482-2 | 84.7mm Base assembly | 7 |
| Bases | | 2359482-3 | 84.7mm Base assembly, w/vent | 5 |
| B | | 2359482-4 | 84.7mm Base assembly | 5 |
| | | 2359482-5 | 84.7mm Base assembly, w/vent | 3 |
| | | 2359482-6 | 84.7mm Base assembly | 3 |

| | | Part number | Description | Height | Color |
|--------|--|-------------|-------------------------|--------|------------|
| Covers | | 2359615-1 | Cover, light controller | 58.6mm | Smoke gray |
| | | 2359615-2 | Cover, light controller | 58.6mm | Light gray |
| | | 2359615-3 | Cover, light controller | 98mm | Smoke gray |
| | | 2359615-4 | Cover, light controller | 98mm | Light gray |
| | | 2359615-5 | Cover, light controller | 58.6mm | Clear |
| | | 2359615-6 | Cover, light controller | 98mm | Clear |
| | | 1-2359615-1 | Cover, light controller | 58.6mm | Blue |