

KCMA-44-1000-5A-5VA-1**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Cable-type current transformer**

The cable-type current transformer is mainly used for retrofitting in order to avoid cutting the primary conductors.

Due to its dimensions and the convenient handling, the cable-type current transformer is particularly suitable for use in places that are difficult to access or where space is limited.

The "click" system in conjunction with the fixing clamps even makes "one-handed" installation possible.

General ordering data

| | |
|------------|--|
| Version | Primary current: 1000 A, Secondary current max.: 5 A, Load: 5 VA, Tolerance class: 1, Split-core current transformer |
| Order No. | 2437400000 |
| Type | KCMA-44-1000-5A-5VA-1 |
| GTIN (EAN) | 4050118450606 |
| Qty. | 1 pc(s). |

Creation date September 17, 2022 10:17:15 PM CEST

Catalogue status 09.09.2022 / We reserve the right to make technical changes.

KCMA-44-1000-5A-5VA-1

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|----------|-----------------|------------|
| Depth | 98 mm | Depth (inches) | 3.858 inch |
| Height | 120.6 mm | Height (inches) | 4.748 inch |
| Width | 72.2 mm | Width (inches) | 2.843 inch |
| Net weight | 662 g | | |

Temperatures

| | | | |
|---------------------|----------------|-----------------------|---------------|
| Storage temperature | -25 °C...70 °C | Operating temperature | -5 °C...50 °C |
|---------------------|----------------|-----------------------|---------------|

Dimensions of live conductors

| | | | |
|-----------------------|--------------------------|-----------------|-------|
| Type of conductor | Insulated conductor only | Round conductor | 44 mm |
| Installation location | Indoor use | | |

Electrical attributes

| | | | |
|------------------------|------|-----------------|---------|
| Load | 5 VA | Primary current | 1,000 A |
| Secondary current max. | 5 A | Tolerance class | 1 |

Technical data

| | | | |
|-------------------|------------------------------|---------|--------------------------------|
| Protection degree | IP20 | Version | Split-core current transformer |
| Standards | EN 60044 -1, VDE 0414 Teil 1 | | |

Insulation coordination

| | | | |
|----------|--------------------------------------|-----------------|---|
| Standard | IEC 61869-1: 2007, IEC 61869-2: 2012 | Tolerance class | 1 |
|----------|--------------------------------------|-----------------|---|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002048 | ETIM 7.0 | EC002048 |
| ETIM 8.0 | EC002048 | ECLASS 9.0 | 27-21-09-02 |
| ECLASS 9.1 | 27-21-09-02 | ECLASS 10.0 | 27-21-09-02 |
| ECLASS 11.0 | 27-21-09-02 | ECLASS 12.0 | 27-21-09-02 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|---|---|
| Approval/Certificate/Document of Conformity | KBR-KBU-Konformitätserklärung |
| User Documentation | Instruction sheet German |
| Catalogues | Catalogues in PDF-format |