



**SPECIFICATIONS**

**Electrical Ratings**

**Switching Loads:** 1.5 mA at 115 Vac, resistive; 150 mA at 14 Vdc, resistive  
**Current Carrying Capacity:** 250 mA maximum at 28 Vdc, resistive load  
**Contact Resistance:** 75 mΩ, typical  
**Insulation Resistance:** 1000 mΩ minimum between terminals  
**Voltage Breakdown:** 1000 Vac minimum between terminals  
**Life Expectancy:** 100,000 cycles of operation at rated loads. One cycle of operation is a rotation through all of the active positions and a return to the starting position.


**Mechanical Ratings**

**Rotational Torque:** 2 to 6 in-oz  
**Operating Temperature Range:** -40 C° to +85 C°  
**Storage Temperature Range:** -65 C° to +85 C°  
**Continuous Rotation:** All standard switches are continuous rotation. Desired stop locations supplied upon request.  
**Anti-Rotation Device:** Integral non-turn tab, flatted bushing, .375" diameter, .320 double "D" across flats.  
**Termination:** Standard is PC style, parallel to shaft, facing rear. Options include PC, parallel to shaft, facing front.  
**Panel Mounting Torque:** 10 in-lbs maximum

**Materials and Finishes**

**Bushing/Housing and Shaft/Rotor:** Reinforced thermoplastic  
**Detent Ball:** Stainless steel, nickel-plated  
**Detent Spring:** Tinned music wire  
**Contacts:** Beryllium copper, gold plate over nickel  
**Terminals:** Copper alloy, #725, 100% tin plate over nickel plate  
**Output Board:** FR-4, copper/nickel-plated  
**Mounting Nut:** Brass, tin/zinc-plated hex nut  
**Mounting Bracket:** Stainless Steel, tin-plated

**ORDERING INFORMATION**



**Series:** 25L = Economical, single deck encoder  
**Housing Color:** B = Black housing; R = Red housing  
**Angle of Throw:** 10 = 10°, 36 positions; 11 = 11.25°, 32 positions; 15 = 15°, 24 positions; 18 = 18°, 20 positions; 22 = 22.5°, 16 positions; 30 = 30°, 12 positions; 45 = 45°, 8 positions  
**Mounting Bracket:** Z = with bracket, Blank = no bracket  
**Code Output:** H = Hexadecimal available only in 22.5°  
 G = Gray available only in 22.5°  
 Q = Quadrature (2-bit)

Custom materials, styles, color and markings are available. Custom knobs available, see page I-57.

**Available from your local Grayhill Distributor.** For prices and discounts, contact a local Sales Office, an authorized local Distributor or Grayhill. **For Custom codes. Termination, Tirque, Angles of Throw, Call Grayhill for more information.**

Optical and Mechanical Encoders