

UV66-BAS-7-IPPC-1001.01**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The built-in IPPC 1000 is an entry-level industrial Panel PC. The robust and durable operating touch panels are available from 7" to 15.6" with resistive single- or capacitive multi-touch (BASIC or ADVANCED version).

Two Ethernet 10/100/1000Mbps ports with "Wake on Lan" support and multiple USB ports offer state-of-the-art-connectivity of the IPPC 1000. For data storage, the IPPC 1000 includes a 60GB SSD hard drive and a CFast card slot with external access. Equipped with the Intel Celeron™ J1900 2GHz 64 bit quad-core processor, 4GB RAM memory and the Windows 10 IoT Enterprise 2019 operating system, IPPC 1000 product family can be used in many ways.

General ordering data

Version	Industrial Panel-PC, Display size 7", Resistive touch, Front protection IP66
Order No.	2676430000
Type	UV66-BAS-7-IPPC-1001.01
GTIN (EAN)	4050118750225
Qty.	1 pc(s).

Creation date September 18, 2022 1:15:21 AM CEST

Catalogue status 09.09.2022 / We reserve the right to make technical changes.

UV66-BAS-7-IPPC-1001.01

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	79 mm	Depth (inches)	3.11 inch
Height	167 mm	Height (inches)	6.575 inch
Width	215 mm	Width (inches)	8.465 inch
Wall thickness, min.	2 mm	Wall thickness, max.	6 mm
Net weight	1,800 g		

Temperatures

Storage temperature	-20 °C ... +60 °C	Operating temperature	0 °C ... +50 °C
Humidity	80 % relative humidity (without condensation)		

Equipment

Angle (horizontal)	Left: 80° / Right: 80°	Angle (vertical)	Top: 80° / Bottom: 80°
Luminance	400 cd/m ²	Material display	Plastic
Material frame	Aluminium	Number of displayable colours	16 M
Resolution	800 x 480	Size	7 "
Touch-Screen	resistive		

General data

Current consumption	Voltage	24 V
	Current	1.08 A
Operating system	Windows 10 IoT Enterprise LTSC 2019 64bit	
Protection degree	IP66	
Voltage supply	24 V DC (18-32 V DC) isolated	

System data

Interfaces behind	2 x Ethernet 10/100/1000 MBit/s (RJ45), 1x USB 3.0, 1x USB 2.0, 1x Cfast slot	Interfaces in front	1x USB 2.0
Memory	60 GB mSATA SSD	Memory (RAM)	4 GB, DDR3
Operating system	Windows 10 IoT Enterprise LTSC 2019 64bit	Processor	Intel® Celeron® J1900 - Quad Core 2.0 GHz (2.42 GHz Burst)

Classifications

ETIM 6.0	EC001414	ETIM 7.0	EC001414
ETIM 8.0	EC001414	ECLASS 9.0	19-20-01-03
ECLASS 9.1	19-20-01-03	ECLASS 10.0	19-20-01-03
ECLASS 11.0	19-20-01-03	ECLASS 12.0	19-20-01-03