


CMA-31-125-5A-2,5VA-0,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Plug-on current transformers**

Plug-on current transformers are especially suitable for mounting on the busbar.

The advantages of this type are: screwless connection technology with tension clamp connection, time-saving connection option for solid and flexible conductors, shock-resistant and vibration-proof, high mechanical holding forces and high current resistance.

General ordering data

Version	Primary current: 125 A, Secondary current max.: 5 A, Load: 2.5 VA, Tolerance class: 0,5, closed current transformer
Order No.	2680200000
Type	CMA-31-125-5A-2,5VA-0,5
GTIN (EAN)	4050118696578
Qty.	1 pc(s).

Creation date September 18, 2022 1:23:12 AM CEST

Catalogue status 09.09.2022 / We reserve the right to make technical changes.

CMA-31-125-5A-2,5VA-0,5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight 290 g

Dimensions of live conductors

Type of conductor	Insulated conductor only	Round conductor	25.7 mm
Rail	30 x 10 mm, 25 x 12 mm, 20 x 20 mm	Installation location	Indoor use

Electrical attributes

Load	2.5 VA	Primary current	125 A
Secondary current max.	5 A	Tolerance class	0,5

Technical data

Version closed current transformer

Insulation coordination

Standard	IEC 61869-1: 2007, IEC 61869-2: 2012	Tolerance class	0,5
----------	---	-----------------	-----

Classifications

ETIM 6.0	EC002048	ETIM 7.0	EC002048
ETIM 8.0	EC002048	ECLASS 9.0	27-21-09-02
ECLASS 9.1	27-21-09-02	ECLASS 10.0	27-21-09-02
ECLASS 11.0	27-21-09-02	ECLASS 12.0	27-21-09-02

Approvals

ROHS Conform

Downloads

Approval/Certificate/Document of Conformity	UL- certificate
Catalogues	Catalogues in PDF-format