

**CMA-101-2500-5A-10VA-0,5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Plug-on current transformers**

Plug-on current transformers are especially suitable for mounting on the busbar.

The advantages of this type are: screwless connection technology with tension clamp connection, time-saving connection option for solid and flexible conductors, shock-resistant and vibration-proof, high mechanical holding forces and high current resistance.

**General ordering data**

Version	Primary current: 2500 A, Secondary current max.: 5 A, Load: 10 VA, Tolerance class: 0,5, closed current transformer
Order No.	<a href="#">2680250000</a>
Type	CMA-101-2500-5A-10VA-0,5
GTIN (EAN)	4050118696608
Qty.	1 pc(s).

Creation date September 18, 2022 1:24:10 AM CEST

Catalogue status 09.09.2022 / We reserve the right to make technical changes.

**CMA-101-2500-5A-10VA-0,5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Length	147 mm	Length (inches)	5.787 inch
Net weight	660 g		

**Dimensions of live conductors**

Type of conductor	Insulated conductor only	Round conductor	70 mm
Rail	100 x 10 mm, 80 x 30 mm	Installation location	Indoor use

**Electrical attributes**

Load	10 VA	Primary current	2,500 A
Secondary current max.	5 A	Tolerance class	0,5

**Technical data**

Version	closed current transformer
---------	----------------------------

**Insulation coordination**

Tolerance class	0,5
-----------------	-----

**Classifications**

ETIM 6.0	EC002048	ETIM 7.0	EC002048
ETIM 8.0	EC002048	ECLASS 9.0	27-21-09-02
ECLASS 9.1	27-21-09-02	ECLASS 10.0	27-21-09-02
ECLASS 11.0	27-21-09-02	ECLASS 12.0	27-21-09-02

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Catalogues	<a href="#">Catalogues in PDF-format</a>
------------	--