

IE-SR-2TX-WL-4G-US-V

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



Weidmüller Industrial Security Routers

- Easy integration of subnets with identical IP address ranges through 1:1 NAT
- Secure and easy remote maintenance with Weidmüller u-link remote access service
- Future-proof network connection with static and dynamic routing
- Increased network security through stateful inspection firewall, IP/Port- forwarding and network segmentation
- Secure communication over the Internet by using IPsec and OpenVPN
- Reliable internet connection, even without on-site internet access, thanks to integrated 4G/LTE cellular modem
- Full flexibility thanks to Fast Ethernet and Gigabit Ethernet interfaces ranging from 2 up to 6 ports.

General ordering data

Version	Security/NAT/VPN Router, with integrated multi-band modem (4G/3G), US-model, Fast Ethernet, 2x RJ45 10/100BASE-T(X), 1x DB9 male for RS-232/422/485, IP30, -25 °C...70 °C
Order No.	2682580000
Type	IE-SR-2TX-WL-4G-US-V
GTIN (EAN)	4050118692136
Qty.	1 pc(s).

IE-SR-2TX-WL-4G-US-V

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Technical data

Dimensions and weights

Depth	81 mm	Depth (inches)	3.189 inch
Height	95 mm	Height (inches)	3.74 inch
Width	45 mm	Width (inches)	1.772 inch
Net weight	650 g		

Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-25 °C...70 °C
Operating temperature, min.	-25 °C	Operating temperature, max.	70 °C
Humidity	5 to 95 % (non-condensing)		

Mobile radio interface

Frequency band	LTE-FDD: B2, B4, B5, B12, B13, B14, B66, B71, WCDMA: B2,B4,B5		
Transmission rate mobile radio	LTE category	CAT 4	
	Download rate, max.	150 Mbps	
	Upload rate, max.	50 Mbps	
Wireless module	multi-band modem (4G/3G), Region: North America		

EMC conformity and approvals

EMC standards	EN 55032, EN 55024, FCC Part 15 Subpart B Class A, IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV, IEC 61000-4-3 RS: 80 MHz bis 1 Ghz: 3 V/m, IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV, IEC 61000-4-5 Surge: Power: 0,5 kV; Signal: 1 kV, IEC 61000-4-6 CS: 3 Vrms	Free fall	According to IEC 60068-2-31
Safety standard	SELV according to EN 62368-1, UL 61010-1, UL 61010-2-201	Shock	according to IEC 60068-2-27
Vibration	according to IEC 60068-2-6		

Environmental conditions

Humidity	5 to 95 % (non-condensing)		
Operating altitude	Altitude, max.	2,000 m	
	Note	in acc. with UL	
	Altitude, max.	6,000 m	
	Note	for restrictions, see the manufacturer's declaration for operating altitude in section downloads	
Operating temperature, max.	70 °C		
Operating temperature, min.	-25 °C		
Storage temperature, max.	85 °C		
Storage temperature, min.	-40 °C		

Guarantee

Time interval	5 years
---------------	---------

Creation date January 17, 2023 4:08:04 PM CET

Catalogue status 09.01.2023 / We reserve the right to make technical changes.

2

IE-SR-2TX-WL-4G-US-V

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

Technical data

Interfaces

Connector for external antennas	2x SMA female, 1x RP-SMA female	Digital inputs	www.weidmueller.com 1x, 5 to 30 V for logic "1", 0 to 2 V for logic "0"
Digital outputs	1x, with a current capacity of 0.2 A at 30 V DC	Function reset button	<5 sec: System reboot and set LAN IP to factory Default, >5 sec: Factory default
Number of SIM-Card slots	2	Number of ports	2x RJ45 10/100BASE-T(X), 1x DB9 male for RS-232/422/485
SIM-Card slot type	Mini-SIM (ID-000 format)		

MTBF

MTBF	According to Standard	Telcordia SR-332
	Operating time (hours), min.	353,679 h

Management features

Device configuration	Webbrowser (HTTP/HTTPS), SNMP v2c, Command Line Interface (Telnet/SSH), Upload of a configuration file via web-interface, SMS control commands	Monitoring function	SNMP v2c, Syslog, Event based warning via E-Mail, Event based warning via relay, Event based warning via SNMP trap, Event based warning via SMS, Device information and mobile radio status via SMS request
IP-address management	Static, DHCP-Client, DHCP-Server (pool-based), DHCP-Relay, DNS-Relay	Security functions	Access Control List (MAC-based) for WLAN Access Point mode
Time synchronization management	NTP server, NTP client	Operating modes	WLAN Access Point, WLAN Client, Virtual COM mode, TCP Server mode, TCP Client mode, UDP Server/Client mode

Power supply

Connection type	1 removable 4-pin terminal block		
Current consumption	Voltage	12 V DC	
	Current	0.46 A	
	Voltage	24 V DC	
	Current	0.22 A	
	Voltage	48 V DC	
	Current	0.11 A	
Overload current protection	Yes		
Reverse polarity protection	Yes		
Voltage supply	12/24/48 V DC, 2 redundant inputs, or 48 V DC Power-over-Ethernet (IEEE 802.3af)		
Voltage supply range	Voltage type	DC	
	Voltage, min.	10.8 V	
	Voltage, max.	52.8 V	

Routing Features

Firewall functions	Stateful Packet Inspection Firewall (Layer-3)	NAT functions	Source / Destination NAT (Port / Host / Network)
Routing functions	IPv4 routing, Static and dynamic IP Routing	VPN functions	OpenVPN (Server or Client)

Creation date January 17, 2023 4:08:04 PM CET

IE-SR-2TX-WL-4G-US-V

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Technical data

Serial communication parameters

Baud rate	110 bit/s to 460800 bit/s	Data bits	7, 8
Parity	none, odd, even, Mark, Space	Stop bits	1, 2

Technical data

Housing main material	Metal	Protection degree	IP30
Speed	Fast Ethernet	Type of mounting	DIN rail, Wall mounting

Technology

Standard	IEEE 802.3 for 10BASE-T, IEEE 802.3u for 100BASE-TX, IEEE 802.3af for Power-over-Ethernet, IEEE 802.11b/g/n for Wireless LAN
----------	--

WLAN interface

Data security	64-bit and 128-bit WEP encryption, WPA/WPA2 Personal and Enterprise (IEEE 802.1X/RADIUS, TKIP and AES)		
Transmission rate WLAN	Standard	IEEE 802.11b	
	max.	11 Mbps	
	min.	1 Mbps	
	Standard	IEEE 802.11g	
	max.	54 Mbps	
	min.	6 Mbps	
	Standard	IEEE 802.11n	
	max.	150 Mbps	
	min.	6.5 Mbps	

Classifications

ETIM 6.0	EC001478	ETIM 7.0	EC001478
ETIM 8.0	EC001478	ECLASS 9.0	19-17-01-03
ECLASS 9.1	19-17-01-03	ECLASS 10.0	19-17-04-05
ECLASS 11.0	19-17-04-05	ECLASS 12.0	19-17-04-05

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
SCIP	9229992a-00b9-4096-8962-200a7f33e289

Approvals

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate no. (cULus)	E141197

Creation date January 17, 2023 4:08:04 PM CET

Catalogue status 09.01.2023 / We reserve the right to make technical changes.