

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|-------------------------------------|-----------|-----|------|
| | A1 | ADD PART NO | 27OCT2016 | G.F | S.M |
| | B | ECR-18-007442 UPDATE SPEC No | 15MAY2018 | G.F | S.M |
| | B1 | ECR-19-000252 UPDATE WIRE RANGE | 08JAN2019 | G.F | S.M |
| | B2 | ECR-19-003479 UPDATE THE WIRE RANGE | 27FEB2019 | G.F | S.M |

NOTES :

- MATERIALS AND FINISH:
CONTACTS: COPPER ALLOY, FINISH: TIN OVER NICKEL UNDERPLATE
- MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)
- THIS PRODUCT HAS NOT COMPLETED VALIDATION TESTING
- WIRE TYPES AND SIZES ACCEPTED
WIRE SIZE: 18AWG SOLID WIRE
20AWG SOLID & STRANDED
22AWG SOLID & STRANDED
24AWG SOLID WIRE
TIN-DIPPED FOR ALL STRANDED WIRE.
WIRE INSULATION MUST BE OUT THE CONTACT.
STRIP LENGTH: 6.0+/-0.3mm
- PACKAGED IN TAPE & REEL

SCALE 15:1

PART NO: 2834171-3

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN GEORGE FU 27OCT2016

CHK SHI MING 27OCT2016

APVD XU XIANG 27OCT2016

PRODUCT SPEC

108-137190

APPLICATION SPEC

114-137190

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME SMT ULTRAMINUATURE SLIM CONTACT

SIZE A3 CAGE CODE - DRAWING NO C-2834171 RESTRICTED TO -

SCALE 9:1 SHEET 1 OF 1 REV B2

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

| | | |
|--------|---|------|
| 0 PLC | ± | - |
| 1 PLC | ± | 0.20 |
| 2 PLC | ± | 0.13 |
| 3 PLC | ± | - |
| 4 PLC | ± | - |
| ANGLES | ± | - |

MATERIAL TBD

FINISH

-

1470-19 (3/13)