


IMPEDANCE (Z)			
Frequency	25 MHz	100 MHz	300 MHz
Nominal (REF)	150 Ω	260 Ω	410 Ω
Minimum	- Ω	208 Ω	- Ω



AGILENT E4991A Impedance/Material Analyzer
HP 16092A-Test Fixture, REF #3399

NOTES:

- CASE FLAMMABILITY RATING: UL94 V-0
- ASSEMBLED PART #: 28A3851-0A2
- CASE COLOR: -0A2 BLACK CASE.
- CORE DIMENSIONS REFER TO 28A3851-000 SPEC. FERRITE CORE DIMENSION IS FOR INTERNAL PURPOSE TO ENHANCE FITTING TO CASE AND ELECTRICAL CHARACTERISTICS ONLY.
- COSMETIC SPECIFICATION REFER TO WI-QA-038.

CASE DIMENSIONS:

A	30.00 [1.181]	+	1.00 [.039]
B	13.00 [.512]	+	1.00 [.039]
C	33.70 [1.327]	+	1.00 [.039]
C1	38.90 [1.531]	+	1.50 [.059]
D	30.00 [1.181]	+	1.00 [.039]

DIMENSIONS ARE IN mm [INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.					
REV	DESCRIPTION	DATE	INT						REV
K	UPDATE CASE DIMENSIONS REMOVE CORE DIM AND ADD NOTE 4&5	01/13/14	Jcai	PROJECT/PART NUMBER: 28A3851-0A2			K	FERRITE SNAP-ON	JRK
J	REVISE NOTES ADD UL94 V-0 FLAMMABILITY UPDATE COMPANY LOGO	05/05/08	TMB	DATE:	06/29/04	SCALE:	NTS	MATERIAL:	FERRITE
H	UPDATE Z SPECS	06/27/07	JRK	CAD #	28A3851-0A2-K	TOOL #	-		
G	UPDATE COMPANY LOGO	04/19/07	TMB						
F	REMOVE (SPEC) mm [in] FROM CORE & CASE DIMENSION VIEWS REMOVE CORE & CASE P/Ns FROM VIEWS UPDATE NOTES	03/21/07	TMB						
REV	DESCRIPTION	DATE	INT						