



NOTES:

1. PLUG FINGER SAME AS 290
2. PLUG FINGER, HANDLE, STRAIN RELIEF, AND SCREWS ARE SHIPPED UNASSEMBLED.
3. ASSEMBLE STRAIN RELIEF TO HANDLE BEFORE INSERTING CABLE.
4. THIS PRODUCT IS RoHS COMPLIANT.

PARTNUMBER	PART REV	RECOMMENDED STRAIN RELIEF CABLE RANGE
290F	0A	Ø 0.220 - Ø 0.190
290FL	0A	Ø 0.250 - Ø 0.220

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE *	WIDTH *	MULT *	LBS/M *	TEMPER *
					FINISH *			MATERIAL *	
					SPEC No. *			SPEC No. *	
					FIRST USED ON *		SCALE 5:4		
0A	PRELIMINARY	6/19/17	*	*	DATE DRAWN	BY	CHKD	APVD	<b>Switchcraft®</b>
					6/19/17	AB	AB	*	
								SHEET 1 OF 1	
REV	ECO NUMBER	DATE	BY	APVD	NAME			PART No.	REV
REVISIONS					290 FLEX, RoHS			290F - 290FL	0A
DO NOT SCALE DRAWING									

