

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

LOC

DIST

REVISIONS

© COPYRIGHT 20

Tyco Electronics AMP GmbH

ALL RIGHTS RESERVED.

AL

2

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D5	REVISED	21AUG2012	MZ	JC
	D6	REVISED PER ECR-13-009678	18SEP2013	RS	DD
	D7	ECR-16-004670	04APR2016	RS	JL

TYPICAL APPLICATION

Dimensions: 21.9, 9.9, 3.4, 1.8, 9.7, 3.7, 4.2+0.1
 Part numbers: X-293309-X, 1740259-X, 293309-X, 293310-1
 SECTION A-A SCALE 4:1

PRINTED CIRCUIT BOARD LAYOUT FOR LOW VOLTAGE VERSION

TOLERANCES UNLESS OTHERWISE SPECIFIED ± 0.05
PRINTED CIRCUIT BOARD THICKNESS: 1.6 mm NOMINAL

Dimensions: 7.4, 5.6, 4.2+0.1
 Hole diameters: $\phi 1.1 \pm 0.1$ 2x, $\phi 1.5 \pm 0.1$ 2x UNPLATED

PRINTED CIRCUIT BOARD LAYOUT FOR HIGH VOLTAGE VERSION

TOLERANCES UNLESS OTHERWISE SPECIFIED ± 0.05
PRINTED CIRCUIT BOARD THICKNESS: 1.6 mm NOMINAL

Dimensions: 4.2, 1.0, 3, 1, 4, 7.4, 5.6
 Hole diameters: $\phi 1.1 \pm 0.1$ 2x, $\phi 1.5 \pm 0.1$ 2x UNPLATED
 SLOT

HIGH VOLTAGE

KEYING HV-1

KEYING HV-2

KEYING HV-3

LOW VOLTAGE

KEYING LV-1

KEYING LV-2

1) MATERIALS:
 CONTACTS: SOLDERING SIDE TIN PLATED Ph. BRONZE
 RECEPTACLE IN SPECIAL ALLOY COPPER TIN PLATED
 HOUSING: PA66 GFF25 UL 94 V0

2 OBSOLETE

2

2

KEYING	REMARKS	PART NUMBER	REV.	COLOR
LV-2	LOW-VOLT 42 V DC	293311-6	D	YELLOW
LV-1	LOW-VOLT 42 V AC	293311-5	D	LIGHT GREY
HV-2	SWITCH MAX. 7A	293311-4	D	RED
HV-3	HIGH-VOLT 125 V AC	293311-3	D	BLUE
HV-1	HIGH-VOLT 250 V AC	293311-2	D	BLACK
HV-1	HIGH-VOLT 250 V AC	293311-1	D	WHITE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN R. FRABONI 18JUN2007

CHK -

APVD G. TURCO

PRODUCT SPEC 108-94018

APPLICATION SPEC 114-32102

WEIGHT -

CUSTOMER DRAWING

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±0.5
2 PLC	±0.3
3 PLC	±
4 PLC	±
ANGLES	±0.5°
FINISH	-

MATERIAL -

FINISH -

TE Connectivity

7.5 mm PCB CONNECTOR ASSEMBLY
90 DEGREE FEMALE VERSION

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-293311	-

SCALE 5:1 SHEET 1 OF 1 REV D7

1470-19 (3/11)