



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 60169-15; EN 122110; MIL-STD-348A, Fig. 310

Documents

N/A

Material and plating

Connector parts

- Center contact
- Outer contact
- Dielectric
- Coupling nut
- Gasket
- Substrate

Material

- Brass
- Brass
- PTFE
- Brass
- Silicone
- Al₂O₃

Plating

- Gold, min. 1.27 µm, over nickel
- Gold, min. 0.8 µm, over nickel
- Gold, min. 0.15 µm, over chemical nickel

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05.10/6.0

Technical Data Sheet**Rosenberger**SMA
StandardTermination
Plug 0.5 Watt**32S15R-0.5E3****Electrical data**

Frequency range	DC to 12.4 GHz
Return loss	≥ 32.2 dB, DC to 2 GHz ≥ 26.4 dB, 2 GHz to 8 GHz ≥ 21.2 dB, 8 GHz to 12.4 GHz
Impedance	50 Ω
Center contact resistance	≤ 3 mΩ
Outer contact resistance	≤ 2 mΩ
Impulse Power (1μs, 1%)	100 Watts at 25°C environment temperature
Power handling	0.5 W at 25°C derated linearity to 0 Watts at 155°C

Mechanical data

Mating cycles	≥ 100
Coupling nut retention	≥ 180 N
Maximum torque	0.60 Nm
Recommended torque	0.50 Nm

Environmental data

Temperature range	-55 °C to +155 °C
2002/95/EC (RoHS)	compliant

Packing

Standard	100 pcs in blister
Weight	3.4 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Kerstin Herzog	10/02/05	Frank Weiß	05/03/13	b00	13-0254	Marion Striegler	05/03/13
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0 Fax : +49 8684 18-499 Email : info@rosenberger.de			Page 2 / 2