A range of high quality UK manufactured phono plug made from machined brass with various plating options. The aluminium housing is anodised in various colours for easy identification.

- -Centre contact is a solid pin with a large scalloped solder bucket.
- -Grounded contact with precision machined 'T' shape slot for maximum contact.
- -Cable clamp for cable gripping and dual grounding.
- -Attractive body styling.

Material

Centre Contact

:Brass

: Brass

Flash gold plate

Grounded Contact

Flash gold plate

Insulation : PTFE Collet : Brass,

flash gold plate

Phono Cap : Brass

Black chrome plate

Ratings-

Rated Current: 5A. Rated Voltage: 50V. Insulation resistance 100m W 500 Vdc

Deltron Part No.	Description
346-0100	BLACK ANODISED CAP PLUG
346-0200	BLUE ANODISED CAP PLUG
346-0500	RED ANODISED CAP PLUG
346-0700	YELLOW ANODISED CAP PLUG



PROPRIETARY AND CONTIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF
ALPHA 3 MANUFACTURING.
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION O
ALPHA 3 MANUFACTURING. IS PROJUBITED.

Harareaves Way, Sawcliffe Ind. Park

DIMENSIONS ARE IN MILLIMETRES LINEAR TOLERANCE: NO DECIMAL PLACES ±0.5mm 1 DECIMAL PLACES ±0.25mm 2 DECIMAL PLACES ±0.125mm ANGULAR TOLERANCE: ±1*

UNLESS OTHERWISE SPECIFIED:

FINISH PROFESSIONAL PHONO PLUG SH

IF IN DOUBT ASK
DO NOT SCALE DRAWING

SEE NOTE

MATERIAL

DEBURR AND BREAK SHARP EDGES APPROVED BY WC
THIRD ANGLE PROJECTION SHEET 1 OF 1

TE

A4

GENERAL SPECIFICATION
346 SERIES
PHONO PLUG

346 SERIES

Release