


Steward



CORE DIMENSIONS				35T0375-300			
UNCOATED CORE							
	MM	INCHES		MM	INCHES		
OD	9.53	(.375)	±	.25	(.010)		
ID	4.75	(.187)	±	.25	(.010)		
TH	4.78	(.188)	±	.13	(.005)		
EPOXY COATING				35T0375-30H			
OD	9.68	(.381)	±	.41	(.016)		
ID	4.60	(.181)	±	.41	(.016)		
TH	4.93	(.194)	±	.28	(.011)		

WEIGHT / K 1.2492 KGS 2.7541 LBS
 INITIAL PERMEABILITY **5000**

ROOM TEMPERATURE ELECTRICAL SPECIFICATION									
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	URNS
L1-1T	-20.0%	2.66	3.33	3.99	20.0%	100	4.87	10	1
L1-10T	-20.0%	266.3	332.8	399.4	20.0%	100	48.7	10	10
Q		-							

COATING SPECIFICATIONS			
TYPE	Max. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
Epoxy	(0.1524 / 6.0)	1000	.83

NOTES:



Rev	Description	Date	INT
A	Original Draft	1/5/1998	IS
B	BROCHURE 58 REV 2 12/2004	1/14/2005	TPM
C	CHANGE COATING FROM POLY TO EPOXY, Revised Template	5/16/2006	WMM

Date:5/15/2006	DWG # 35T0375-30H-C	Rev:
Drawn By: WMM	Title # 35T0375-30H	C

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT