

**MODLINK MSDD SINGLE COMBI INSERT USA NEMA 5-15**

1xSUD-D9 female/female + 1xRJ45 female/female

1 × NEMA 5-15 (plug-solder connection)  
 1 × RJ45, 8-pole metal, CAT5e (female/female)  
 1 × SUB-D9 (female/female)

**Link to Product****Illustration**

Product may differ from Image

**General data**

Dimensions HxWxD 88x51x30 mm

**Classifications**

ECLASS-6.0	27189217
ECLASS-6.1	27189217
ECLASS-7.0	27189217
ECLASS-8.0	27189217
ECLASS-9.0	27182806
ECLASS-10.1	27182806
ECLASS-11.1	27182806
ECLASS-12.0	27182806
ETIM-5.0	EC000020

**USA**

Connection	Plug-solder connection: 4.8x0.5 mm
No. of poles	2 + PE
Operating voltage	125 V AC
Operating current	15 A

**SUB-D9**

Operating voltage	48 V AC/DC
No. of poles	9-pole
Operating current	3 A
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC

Locking of ports	UNC 4...40 bolt
------------------	-----------------

Connection front side	SUB-D (female)
-----------------------	----------------

Operating current (UL Rating)	max. 175 mA
-------------------------------	-------------

Connection rear side	SUB-D (female)
----------------------	----------------

**RJ45**

Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)
---------------	---------------------------------------

Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
-------------------------------	------------------------

Connection rear side	RJ45
----------------------	------

Connection front side	RJ45
-----------------------	------

Locking of ports	Snap In
------------------	---------

Operating current (UL Rating)	max. 175 mA
-------------------------------	-------------

**Commercial data**

customs tariff number	85366990
-----------------------	----------

GTIN	4048879037235
------	---------------

Packaging unit	1
----------------	---