

**MODLINK MSDD SINGLE COMBI INSERT USA NEMA 5-15**

1xSUD-D9 female/male + 1xRJ45 female/female

1 × NEMA 5-15 (plug-solder connection)  
 1 × RJ45, 8-pole metal, CAT5e (female/female)  
 1 × SUB-D9 (female/male)

**Link to Product****Illustration**

Product may differ from Image

**General data**

Dimensions HxWxD 88x51x30 mm

**USA**

Connection	Plug-solder connection: 4.8x0.5 mm
No. of poles	2 + PE
Operating voltage	125 V AC
Operating current	15 A

**SUB-D9**

Operating voltage	48 V AC/DC
No. of poles	9-pole
Operating current	3 A
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Locking of ports	UNC 4...40 bolt
Connection front side	SUB-D (female)
Operating current (UL Rating)	max. 175 mA
Connection rear side	SUB-D (male)

**RJ45**

Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Connection rear side	RJ45
Connection front side	RJ45

---

Locking of ports	Snap In
Operating current (UL Rating)	max. 175 mA