

MODLINK MSDD SINGLE COMBI INSERT USA NEMA 5-15

2xRJ45 female/female

1× NEMA 1-15 (plug-solder connection) 2× RJ45, 8-pole metal, CAT5e (female/female)

Link to Product

Illustration



Product may differ from Image



| General data | |
|-------------------------------|---------------------------------------|
| Dimensions H×W×D | 88×51×25 mm |
| Classifications | |
| ECLASS-6.0 | 27189217 |
| ECLASS-6.1 | 27189217 |
| ECLASS-7.0 | 27189217 |
| ECLASS-8.0 | 27189217 |
| ECLASS-9.0 | 27182806 |
| ECLASS-10.1 | 27182806 |
| ECLASS-11.1 | 27182806 |
| ECLASS-12.0 | 27182806 |
| ETIM-5.0 | EC000020 |
| USA | |
| Connection | Plug-solder connection: 4.8×0.5 mm |
| No. of poles | 2 + PE |
| Operating voltage | 125 V AC |
| Operating current | 15 A |
| RJ45 | |
| Specification | CAT5e, Class D, 100 MHz, (EN 50173-1) |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Connection rear side | RJ45 |
| Connection front side | RJ45 |

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2023-09-15

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com



| Locking of ports | Snap In | |
|-------------------------------|---------------|--|
| Operating current (UL Rating) | max. 175 mA | |
| Commercial data | | |
| customs tariff number | 85366990 | |
| GTIN | 4048879371483 | |
| Packaging unit | 1 | |

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2023-09-15

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | shop@murrinc.com | shop.murrinc.com