

MODLINK MSDD DBL COMBI INSERT USA 2XNEMA 5-15

GFCI+1xRJ45 female/female + 1x3A fuse

2× NEMA-GFCI 5-15 (screw terminals)
 1× RJ45, 8-pole metal, CAT5e (female/female)
 1× fuse (3 A)
 with touch protection

[Link to Product](#)**Illustration**

Product may differ from Image

**General data**

Dimensions H×W×D	88×116×72 mm
------------------	--------------

Classifications

ECLASS-6.0	27189217
ECLASS-6.1	27189217
ECLASS-7.0	27189217
ECLASS-8.0	27189217
ECLASS-9.0	27182806
ECLASS-10.1	27182806
ECLASS-11.1	27182806
ECLASS-12.0	27182806
ETIM-5.0	EC000020

Fuse

Continuous load	3 A
Operating voltage	250 V AC/32 V DC

USA

Connection	Screw terminals: max. 2× 6 mm ² (AWG 10)
No. of poles	2 + PE
Operating voltage	125 V AC
Operating current	15 A

RJ45

Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Connection rear side	RJ45
Connection front side	RJ45
Locking of ports	Snap In
Operating current (UL Rating)	max. 175 mA

Commercial data

customs tariff number	85366990
GTIN	4048879369268
Packaging unit	1