

Fixed Length Cable Assemblies

SMB RIGHT ANGLE PLUG TO SMB RIGHT ANGLE PLUG




| PART NUMBER | CABLE TYPE | CABLE LENGTH | CONNECTOR A | CONNECTOR B |
|--------------|------------|--------------|--------------|--------------|
| 415-0001-006 | RG-178 | 6" | 131-1402-101 | 131-1402-101 |
| 415-0001-012 | RG-178 | 12" | 131-1402-101 | 131-1402-101 |
| 415-0001-018 | RG-178 | 18" | 131-1402-101 | 131-1402-101 |
| 415-0001-024 | RG-178 | 24" | 131-1402-101 | 131-1402-101 |
| 415-0001-030 | RG-178 | 30" | 131-1402-101 | 131-1402-101 |
| 415-0001-036 | RG-178 | 36" | 131-1402-101 | 131-1402-101 |
| 415-0004-006 | RG-316 | 6" | 131-1403-101 | 131-1403-101 |
| 415-0004-012 | RG-316 | 12" | 131-1403-101 | 131-1403-101 |
| 415-0004-018 | RG-316 | 18" | 131-1403-101 | 131-1403-101 |

| PART NUMBER | CABLE TYPE | CABLE LENGTH | CONNECTOR A | CONNECTOR B |
|--------------|------------|--------------|--------------|--------------|
| 415-0004-024 | RG-316 | 24" | 131-1403-101 | 131-1403-101 |
| 415-0004-030 | RG-316 | 30" | 131-1403-101 | 131-1403-101 |
| 415-0004-036 | RG-316 | 36" | 131-1403-101 | 131-1403-101 |
| 415-0006-006 | RG-316 DS | 6" | 131-1404-101 | 131-1404-101 |
| 415-0006-012 | RG-316 DS | 12" | 131-1404-101 | 131-1404-101 |
| 415-0006-018 | RG-316 DS | 18" | 131-1404-101 | 131-1404-101 |
| 415-0006-024 | RG-316 DS | 24" | 131-1404-101 | 131-1404-101 |
| 415-0006-030 | RG-316 DS | 30" | 131-1404-101 | 131-1404-101 |
| 415-0006-036 | RG-316 DS | 36" | 131-1404-101 | 131-1404-101 |

Electrical Ratings

Electrical ratings of a cable assembly are determined by the limiting connector type and cable size.

| Connector | Cable | Connector Impedance (Ohms) | Frequency (GHz) | Dielectric Withstanding Voltage (Vrms) | Working Voltage (Vrms) |
|-----------|--------|----------------------------|-----------------|--|------------------------|
| SMB | RG-178 | 50 | 4 | 750 Vrms | 250 Vrms |
| | RG-316 | 50 | 4 | 1000 Vrms | 335 Vrms |



Johnson Components' cable length applies to the end of straight connectors. The length is applied to the vertical centroid of right angle connectors.

The last three digits of the part number reflect the length of the cable in inches.