



## HE-1400v2

## LCD Controller for Industrial Monitors

Based on the ALR-1400v2 and as a successor to the HE-1400 the HE-1400v2 is a small footprint - designed for industrial LCD monitors and display applications in harsher environments.

#### Key Features:

- » Up to 1440 x 900 input / Up to 1440 x 900 LCD panels
- » DVI, VGA (ARGB)
- » LVDS and TTL panel connection @60Hz
- » Auto EDID setting (new feature)
- » Low latency (input to output)
- » Custom splash-screen option
- » RS-232 (USB\*) for commands & control
- » HE specific: Conformal coating, wider temperature rating.
- » Part number: 4175801xx-3

## **Panel Connectivity**

TTL (dual channel): up to 1440 x 900 @60Hz LVDS (dual channel): up to 1440 x 900 @60Hz

Panel resolutions: Supports common panel resolutions and

timings from 640 x 480 up to 1440 x 900

selected by dip switch.

Customization available for other resolutions.

## Input / Sources

**DVI:** 60Hz VESA standard inputs VGA to SXGA

Widescreen modes: 1280/1360, 1366/1368

CVT modes - coming soon

VGA (ARGB): 60Hz VESA standard inputs VGA to SXGA

Widescreen modes: 1280/1360, 1366/1368

CVT modes - coming soon

**EDID note:** The EDID preferred timing data is automatically set by reference to the LCD panel resolution settings (VESA data). Custom EDID data programming is available as an OEM option.

### Reliability

Calculated MTBF: In excess of 100,000 hours

Warranty: 3 years

#### **Features**

Colors: Up to 8 bit per color, ie 16.7m colors

Function Display: On Screen Display (OSD) menu

Function Controls: External buttons, Serial Port (USB\*) commands

Image Scaling: Up scaling to fit input to panel resolution

Image Control: Brightness, Contrast, Sharpness, Clock, Phase, Color

temperature, Image position, Gamma

Other Features: Auto Image Adjust, Color Auto Adjust, Auto source

seek, OSD timeout, OSD menu position, OSD menu transparency, Input select source, Aspect ratio, Backlight brightness adjustment, Language select

Power:  $+12VDC / +24VDC \pm 5\%$ , 2.5W (controller only)

Panel Power: Supports 3.3V, 5V, 12V & 18V panels
Inverter Support: PWM, D/A DPMS Enable pin (3.3V or 5V)

Plug & Play: DDC 1,2/b compatible

Status Indicator: Dual color LED support

Dimensions: 107mm x 92mm (4.2" x 3.6")

Operating Temp: -20°C to +80°C\*\*

**Custom Splash-screen:** The HE-1400v2 supports a custom splash-screen when powering on. This requires custom firmware.


**Firmware Update:** The firmware version of the HE-1400v2 can be updated using a dedicated USB programming interface available from Digital View, this connects to the DVI input on the HE-1400v2 therefore enabling firmware upgrade on assembled monitors.

\*requires a converter for USB to RS-232, not included \*\*Project & environment suitability must be verified by the user.



# HE-1400v2 LCD Controller for Industrial Monitors

## **Mechanical Drawing**



### **Connector Definitions**

J1 LVDS Panel Signal TTL Panel Signal CN2 CN3 TTL Panel Signal CN8 Serial control CNA<sub>1</sub> **Auxiliary Power Output** CNB<sub>1</sub> Backlight Control connector CNC<sub>1</sub> **OSD Function Controls** LED1 Dual color status LED connector

P1 VGA input P2 DVI-D input PP2 Main Input Power

## **Ordering Options**

#### HE-1400v2

OSD digital button board
OSD membrane kit - Vertical
OSD membrane kit - Horizontal
Inverter interface

## P/N: 4175801xx-3

Kit 67110-3 Kit 67135-3 Kit 67134-3 P/N 416040010-3

### **Drawings**

- » 2D (dwg)
- » 3D (SLDPRT and IGS)

#### Download at:

http://www.digitalview.com/products/he-1400v2-lcd-controller

## **Available Resources**

- » Instruction manual
- » Revision control documentation
- » Firmware upgrade manual\*\*
- » Mechanical drawings
- » Custom engineering: Splash screen, OSD menu, coatings, & more...
- \*\* Available on request

#### **Controller Solution Generator**

http://www.digitalview.com/csg



www.digitalview.com

#### USA

18440 Technology Drive, Morgan Hill, CA 95037, USA t: +1 (408) 782-7773

#### EUROPE

The Lake House, Knebworth Park, Herts, SG3 6PY, UK t: +44 (0) 20-7631-2150

#### ASIA

705-708 Texwood Plaza, 6 Hong Ming St, Kwun Tong, Hong Kong t: (852) 2861-3615