

Kabeltülle PG12, Plug, solder terminal, insulated, 7.5 mm, 6-pole, straight, UK-Connector



Description

- Solder terminal :
for cable mounting
- Data and Signal transfer
- Data and Signal Connectors 6-pole , insulated , straight

References


Last order date: 30.06.2016

Technical Data

Diameter	7.5 mm	Allowable Operation Temperature	-20°C to 70°C
Number of Poles	6-pole	Terminal	solder terminal
Ratings DC	2 A / 12VDC	Housings	insulated
Ratings AC	2 A / 12VAC	Style	straight
Dielectric Strength	1000VDC	Lifetime	50000 Insertions
Insulation Resistance	> 10000 MΩ @ 500VDC		
Material: Housing	black		

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [General Product Information](#)

Dimensions



All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Data and Signal Plug/Sockets	7.5	6-pole	solder terminal	4804.1600

Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging unit 100 Pcs

Accessories

Description



4804.0001
Sleeve black, 5.6 mm

PHASE-OUT