

Voltage Monitoring Relays

50R Series

Single-Phase Voltage Monitor



Description

The 50R series is a single-phase voltage monitor with a voltage-sensing circuit that constantly monitors the single-phase power for a low-voltage condition. When a harmful condition is detected, the MotorSaver® deactivates its output relay after a specified trip delay. The output relay reactivates after power line conditions return to an acceptable level and a specified amount of time has elapsed (restart delay). The trip delay prevents nuisance tripping due to rapidly fluctuating power line conditions. This monitor is used in a variety of applications such as compressors, air conditioners, heat pumps, well pumps, sump pumps, and small conveyer motors.

Features & Benefits

FEATURES	BENEFITS
Proprietary voltage sensing circuitry	Constant monitoring of single-phase power for a low-voltage condition
Adjustable trip delay (-3 models) and restart delay (-2 models) settings	Prevents nuisance tripping due to rapidly fluctuating power line conditions, allows staggered start-up of multiple motors after a fault
High-voltage detection (-9 models)	Trips and resets at a fixed percentage of the setpoint: trip 110%, reset 107%
600 V rated relay contacts available on some models	Eliminates the need for a control transformer to step voltage down to 120–240 V for a control circuit

Applications

- Fan motors
- Air conditioners
- Compressors
- Heat, well, and sump pumps
- Small conveyer motors

Voltage Monitoring Relays

50R Series

Specifications

Input Characteristics

Line Voltage

50R-100	95–120 V ac
50R200	190–240 V ac
50R400	380–480 V ac

Frequency

50*/60 Hz

Functional Characteristics

Low Voltage

Trip (% of setpoint)	90%
Reset (% of setpoint)	93%

Delay Time (Nominal) Trip

4 seconds

Restart (low voltage)

2 seconds

Restart (complete power loss)

2 seconds

Output Characteristics

Output Contact Rating

(SPDT - 1 Form C)

50R-100, 50R200

Pilot Duty	480 VA @ 240 V ac
General Purpose	10 A @ 240 V ac

50R400

Pilot Duty	470 VA @ 600 V ac
-------------------	-------------------

General Characteristics

Ambient Temperature Range

Operating	-20°C to 70 °C (-4 °F to 158 °F)
Storage	-40 °C to 80 °C (-40 °F to 176 °F)

Maximum Input Power

5 W

Relative Humidity

10–95%, non-condensing per IEC 68-2-3

Terminal Torque

7 in.-lbs.

Wire Size

12–18AWG

Electrostatic Discharge (ESD)

IEC 61000-4-2, Level 3, 6 kV contact, 8 kV air

Fast Transient Burst

IEC 61000-4-4, Level 3, 3.5 kV input power and controls

Transient Protection (Internal)

IEC 61000-4-5; 1995 ±6 kV

Dimensions

H 74.4 mm (2.93"); **W** 133.9 mm (5.27"); **D** 74.9 mm (2.95")

Weight

0.98 lb. (15.68 oz., 444.52 g)

Mounting Method

#8 screws

Special Options

Opt. 2: Variable Restart Delay

Manual, 2–300 seconds

Opt. 3: Variable Trip Delay

2–30 seconds

Opt. 9: High Voltage Detection

Operating Points

Trip (% of Setpoint)	110%
Reset (% of Setpoint)	107%

*Note: 50 Hz will increase all delay timers by 20%

Certification & Compliance

UL	UL 508 (File #E68520)
CE	IEC 60947-6-2